

Table of Contents

Letter of Transmittal	
Corporate Authorization	
Executive Summary	i

1.0	Introduction	1
1.1	General	1
1.2	Background	1
2.0	Design Guidelines / Modeling Parameters	2
2.1	Design Guidelines	2
2.2	Runoff Modeling Parameters	3
3.0	Existing Drainage System	4
3.1	Existing Drainage Patterns	4
3.2	Existing Catchment Areas	4
4.0	Post-Development Drainage System	5
4.1	Post-Development Drainage Patterns	5
4.2	Post-Development Catchment Areas	5
5.0	Runoff Calculations	6
5.1	Pre-Development Runoff Rate	6
5.2	Post-Development Runoff Calculations	6
6.0	Stormwater Management Plan	7
6.1	Conveyance System Design	7
6.2	Stormwater Management Facility Design	7
7.0	Closure	8
8.0	References	9

Appendices

Appendix A	Post-development Model
------------	------------------------

Figures

Figure 1.1	Proposed Layout
Figure 1.2	Existing Topography
Figure 3.1	Existing Drainage Patterns
Figure 4.1	Proposed Catchment Areas
Figure 6.1	Stormwater Conveyance System
Figure 6.2	Stormwater Management Facility

1.0 Introduction

1.1 General

The purpose of this report is to develop a conceptual stormwater management system for controlling the increase in stormwater runoff generated by the proposed build out of the Medicine Valley Industrial Park, in Lacombe County bordering on the north boundary of the Town of Eckville. This report focuses on drainage pattern impact, stormwater quantity changes and stormwater management issues for the subject area.

1.2 Background

The proposed development is approximately 23.9 ha (59 acres) located in the S.E. $\frac{1}{4}$ Section 21-39-3-W5M, as shown in Figure 1.1. The proposed development is located in Lacombe County, bordering the north boundary of the Town of Eckville, west of Secondary Highway 766. The project is to be developed in three phases. Phase 1 and 2 are proposed for commercial and light industrial use. Lot sizes range from 0.4 to 1.6 acres. Phase 3 of the Medicine Valley Industrial park is proposed for residential use.

For the purposes of this study, analysis will exclude the third phase as it is slated for future development. The stormwater management of Phase 3 is assumed to be controlled separately within the residential development, due to the fact it drains to the southwest away from Phases 1 and 2. Note, the developable area of Phase 1 and 2 comprises a total of 18.3 ha.

The land is presently used for agriculture. The development will be made up of several commercial/light industrial lots. The type of development and relatively flat topography will allow for minimal changes in the drainage patterns in the area. Proposed roadway construction will change the drainage patterns within the development, by diverting storm runoff along the roadways. However, the ultimate stormwater discharge location of the area remains roughly the same, though flows will be released at a singular point to the northeast rather than overland over a larger general area.

Topographical information for the development was obtained. This information was used to develop the contour plan of the site, as shown in Figure 1.2.

2.0 Design Guidelines / Modeling Parameters

2.1 Design Guidelines

The following sources were used in determining design guidelines and modeling parameters for this report:

- The City of Red Deer Design Guidelines – Section 10 - Stormwater Management Drainage Systems – City of Red Deer – 2006
- Standards and Guidelines for Municipal Waterworks, Wastewater and Storm Drainage Systems – Alberta Environment – 2006
- Stormwater Management Guidelines for the Province of Alberta – Alberta Environmental Protection – 1999
- Hidden Springs Area Structure Plan – Engineering Support Study – ISL Engineering and Land Services Ltd. – 2005
- Energy Business Park – Stormwater Management Plan – ISL Engineering and Land Services Ltd. – 2008

From these sources, the following guidelines were determined:

- Post-development runoff rates to adjacent areas will not exceed pre-development rates.
- Quality of post-development runoff must be sufficient so as not to degrade the quality of surface water or groundwater in the area as per Alberta Environment. This requires 85% removal of particles 75 microns and larger.
- A pre-development flow rate of 3.6 L/s/ha
- Storm sewers conveying pond outlet flows will be sized based on the post development rate to control flows to acceptable levels.
- Storm pond sized for the 1:100 year event.
- Dry Pond design specifications as follows:
 - o 1.5m maximum storage depth during the 1:100 year event.
 - o Pond volume determined by the 1:100 year Chicago Storm.
 - o Grading details as per the City of Red Deer Design Guidelines.
 - o Minimum freeboard of 0.6 m and Maximum interior slopes of 5:1, as per City of Red Deer Stormwater Management Drainage Systems.

2.2 Runoff Modeling Parameters

In determining the runoff from the catchments in this development, the hydrologic “Runoff” component of the software XP-SWMM was used. For this model, several criteria needed to be identified.

Impervious percentages for land-use types were used as follows (note that for XP-SWMM modeling using the Runoff Method, runoff occurs from 100% pervious areas):

- | | |
|---------------------------------|------|
| • Undeveloped | 20% |
| • Gravel Streets | 65% |
| • Commercial / Light Industrial | 80% |
| • Storm Pond | 100% |

The following infiltration parameters were used:

- | | |
|--|------------------------------|
| • Initial Infiltration Rate | $F_0 = 75 \text{ mm/hr}$ |
| • Asymptotic Infiltration Rate (Final) | $F_C = 7.5 \text{ mm/hr}$ |
| • Infiltration Decay Rate | $k = 0.00115 \text{ s}^{-1}$ |

The following parameters pertaining to depression storage were used:

- | | |
|--------------------------------------|--------|
| • Pervious Area Depression Storage | 3.2 mm |
| • Impervious Area Depression Storage | 1.6 mm |

Additionally, Manning’s “n” values of 0.016 and 0.25 were used for pervious areas and impervious areas respectively. Catchment slopes were determined from topographic information and catchment widths were estimated from a map of the area.

3.0 Existing Drainage System

3.1 Existing Drainage Patterns

Drainage patterns for the site have been determined using contour information. These drainage patterns are shown in Figure 3.1. Sub drainage areas are described as follows:

- Area 1 drains to the southwest.
- Area 2 drains northeast away from higher land in the south and west.
- Area 3 drains generally to the northeast towards Medicine River.
- Area 4 drains slightly to the southeast corner of the area away from higher land in the north.

Ultimately, runoff from the entire development drains into Medicine River northeast of the development area. Based on topographical information and existing roads, it is assumed that there is no offsite drainage incorporated into this stormwater management plan.

3.2 Existing Catchment Areas

Under existing pre-development conditions, the development area naturally drains to Medicine River in the northeast.

4.0 Post-Development Drainage System

4.1 Post-Development Drainage Patterns

The development area is assumed to utilize a Stormwater Management Facility (SWMF) to control the post development storm flows. The development area is graded to convey flows to the SWMF. Overall discharge will be maintained through a surface drainage system (ditch and culvert) that will convey the storm flows from the development area and discharges into the proposed SWMF. It should be noted the SWMF within the project area ultimately discharges to Medicine River via the ditch along Secondary Highway 766.

4.2 Post-Development Catchment Areas

The catchment area delineation was assumed for modeling purposes, with drainage to the proposed pond location in the absence of a grading plan. Post-development drainage patterns assumed are shown in Figure 4.1.

5.0 Runoff Calculations

5.1 Pre-Development Runoff Rate

ISL completed an analysis of the Medicine River hydrology data and utilizing comparative basin formula to calculate a release rate of 1.88 L/s/ha whereas the Waskasoo Creek near Red Deer delivered a rate of 7.87 L/s/ha. Due to inconsistency in stream flow analysis, additional documentation was reviewed. These included:

- 1) Hidden Springs Area Structure Plan – Engineering Support Study, ISL 2005 - The pre-development rate of 3.3 L/s/ha with SCS modeling.
- 2) Energy Business Park - Stormwater Management Plan, ISL 2008 – The pre-development rate of 3.6 L/s/ha with SCS modeling.
- 3) The City of Red Deer Standards - The pre-development rate of 3.6 L/s/ha.

Based on the reviewed documentation, ISL concluded that using a release rate of 3.6L/s/ha would be considered reasonable.

5.2 Post-Development Runoff Calculations

XP-SWMM 2009, a sophisticated hydrologic/hydraulic computer model, was employed to determine the post-development runoff peak rate as well as total runoff expected from the development. Based on modeling results, the post-development peak runoff rate was estimated for each area. The modeled post-development runoff rate for the project area is 145 L/s/ha (Roughly 40 times the prescribed release rate). This post development release rate forms the justification for the conveyance of stormwater and the stormwater management system plan detailed below.

6.0 Stormwater Management Plan

6.1 Conveyance System Design

The layout of the proposed conveyance system is shown in Figure 6.1. The SWMF controls the storm flow rates leaving the development area. Flows from the project area are conveyed, by means of surface drainage system (ditches and culverts), to the proposed SWMF in the northeast. The SWMF restricts the storm flows to the pre-development release rate before flows discharge to the Medicine River through downstream overland conveyance elements.

The conceptual stormwater management network was modeled using XP-SWMM 2009 for the 18.26 ha development area. Storm flows are proposed to be conveyed to the SWMF through roadside ditches. In the absence of a grading plan ditch grades are assumed range from 0.6% - 1.5%.

Ditch and culvert sizing is based on the following:

- The 1:100 year flows along each roadway drain into ditches, which then convey the flows to the SWMF.
- Ditch geometry based on an assumed cross section of 3:1 and 5:1 side slopes, 1 m ditch bottom. Cross section geometry is based on the City of Red Deer Rural Service Road Drawing 5.13.
- Culverts are utilized to convey flows under roadways. Culvert diameters range from 900 -1500 mm in diameter (Only major roadway crossing culverts were sized as part of this analysis).

6.2 Stormwater Management Facility Design

Managing the increased flow rates from the development area, and maintaining stormwater quality control will be achieved through a proposed dry pond and oil and grit separator. The dry pond was selected as the desired SWMF because it will easily incorporate into a potential park area, will not have standing water, should require less maintenance, and will require less surface area than a wet pond, as desired by the Iron Horse Holdings.

The dry pond will outfall to the Medicine River via a naturalized drainage outlet. Stormwater quality will be managed through extended drawdown times as well as the provision of the forebay. This should ensure that stormwater quality will meet Alberta Environment requirements on discharge.

The stormwater management facility design details determined from model results are as follows:

SWMF (Dry pond)

- Catchment Area of 18.3 ha
- Required Storage volume of 8,600 m³
- Peak outlet rate of 58.2 L/s (orifice plate size of 0.029 m² – diameter of 192 mm)
- Maximum depth of 1.16 m
- Side slopes of 5:1
- Requires oil/grit separator for quality control, sized to provide the Alberta Environment requirement of 85% of particles 75 microns or larger on an annual basis.

Figure 6.2 shows the pond location and footprint as modeled.

7.0 Closure

This report was prepared for the proposed Medicine Valley Industrial Park in Lacombe County, adjacent to the Town of Eckville, for the purpose of conceptually designing the stormwater management system for the initial development Phases of the proposed development.

8.0 References

Alberta Environment. 2006. Standards and Guidelines for Municipal Waterworks, Wastewater, and Storm Drainage Systems.


Alberta Environmental Protection. 1999. Stormwater Management Guidelines for the Province of Alberta.

City of City of Red Deer. 2006. Design Guidelines – Section 10 – Stormwater Design Standards.

ISL Engineering and Land Services Ltd. 2005. Hidden Springs Area Structure Plan – Engineering Support Study.

ISL Engineering and Land Services Ltd. 2008. Energy Business Park – Stormwater Management Plan.

Figure 1.1




Legend

- PROPOSED SWMF
- PROJECT AREA

IRON HORSE HOLDINGS Medicine Valley Industrial Park Stormwater Management Plan

PROPOSED LAYOUT

Figure 1.2



Legend

- PROPOSED SWMF
- PROJECT AREA

IRON HORSE HOLDINGS
Medicine Valley Industrial Park
Stormwater Management Plan

EXISTING TOPOGRAPHY





Figure 3.1



Legend

- PROPOSED SWMF
- PROJECT AREA
- GENERAL FLOW DIRECTION
- EXISTING CATCHMENTS


IRON HORSE HOLDINGS Medicine Valley Industrial Park Stormwater Management Plan

EXISTING DRAINAGE PATTERNS

1: 2000 0 20 40 60 80



Figure 4.1



Legend

- PROPOSED SWMF
- PROJECT AREA
- GENERAL FLOW DIRECTION
- CATCHMENT AREA

IRON HORSE HOLDINGS
Medicine Valley Industrial Park
Stormwater Management Plan

PROPOSED CATCHMENT AREAS





Figure 6.1



Legend

- PROPOSED SWMF
- PROJECT AREA
- PROPOSED DITCH CONVEYANCE
- PROPOSED SWMF
- PROPOSED CULVERT
- PROPOSED OUTLET

IRON HORSE HOLDINGS
Medicine Valley Industrial Park
Stormwater Management Plan
STORMWATER CONVEYANCE
SYSTEM





Figure 6.2



Legend

- PROPOSED SWMF
- PROJECT AREA
- PROPOSED OUTLET

IRON HORSE HOLDINGS Medicine Valley Industrial Park Stormwater Management Plan STORMWATER MANAGEMENT FACILITY



Appendix A

Post Development Model

12851_Storm Model.out
Current Directory: C:\XPS\XPSWMM~3
Engine Name: C:\XPS\XPSWMM~3\SWMMEN~1.EXE

Input File : C:_models\12851_Medicine V\12851_Storm Model.XP

```
*=====*
```

xpswmm	
Storm and Wastewater Management Model	
Developed by XP Software Inc.	
=====	
Last Update	: January, 2009
Interface Version:	11.0
Engine Version	: 2009.0
Data File Version:	12.1
Serial Number	:

```
*=====*
```

Engine Name: C:\XPS\XPSWMM~3\SWMMEN~1.EXE

```
*=====*
```

Input and Output file names by Layer

```
*=====*
```

Input File to Layer # 1 JIN.US

Output File to Layer # 1 C:_models\12851_Medicine V\12851_Storm Model.int

Input File to Layer # 2 C:_models\12851_Medicine V\12851_Storm Model.int

Output File to Layer # 2 JOT.US

```
*=====*
```

Special command line arguments in XP-SWMM2000. This now includes program defaults. \$keywords are the program defaults. Other keywords are from the SWMMCOM.CFG file. or the command line or any cfg file on the command line. Examples include these in the file xpswm.bat under the section :solve or in the windows version XPSWMM32 in the file solve.bat

Note: the cfg file should be in the subdirectory swm xp or defined by the set variable in the xpswm.bat file. Some examples of the command lines possible

```
*=====*
```

are shown below:

```
swmmd swmmcom.cfg
swmmd my.cfg
swmmd nokeys nconv5 perv extranwq
```

```
=====
$powerstation      0.0000      1      2
$perv              0.0000      0      4
$oldegg            0.0000      0      7
$as                0.0000      0     11
$noflat            0.0000      0     21
$oldomega          0.0000      0     24
$oldvol            0.0000      1     28
$implicit          0.0000      1     29
$oldhot            0.0000      1     31
$oldscs            0.0000      0     33
$flood             0.0000      1     40
$nokeys            0.0000      0     42
$pzero             0.0000      0     55
$oldvol2           0.0000      2     59
$storage2          0.0000      3     62
$oldhot1           0.0000      1     63
$pumpwpt           0.0000      1     70
$ecloss            0.0000      1     77
$exout             0.0000      0     97
$spatial = 0.90    0.9000      5    124
$djref = -1.0      -0.1000     3    143
$weirlen = 50      50.0000     1    153
$oldbnd            0.0000      1    154
$nogrelev          0.0000      1    161
$ncmid             0.0000      0    164
$new_n1_97         0.0000      2    290
$best97            0.0000      1    294
$newbound          0.0000      1    295
$q_tol = 0.01      0.0001     1    316
$new_storage       0.0000      1    322
$old_iteration     0.0000      1    333
$minlen=10.0       10.0000     1    346
$review_elevation  0.0000      1    383
$use_half_volume   0.0000      1    385
VERT_WALLS=ON      0.0000      1    389
$min_ts = 1.0      1.0000      1    407
$design_restart = on 0.0000      1    412
$zero_value=1.e-05 0.0000      1    415
$relax_depth = on  0.0000      1    427
$saveallpts = on   0.0000      1    434
=====
```

```
=====
| Parameter Values on the Tapes Common Block. These are the
| values read from the data file and dynamically allocated
| by the model for this simulation.
|=====
```

```
Number of Subcatchments in the Runoff Block (NW).... 12
Number of Channel/Pipes in the Runoff Block (NG).... 0
Runoff Water quality constituents (NRQ)..... 0
Runoff Land Uses per Subcatchment (NLU)..... 0
Number of Elements in the Transport Block (NET)..... 0
Number of Storage Junctions in Transport (NTSE)..... 0
Number of Input Hydrographs in Transport (NTH)..... 0
Number of Elements in the Extran Block (NEE)..... 21
Number of Groundwater Subcatchments in Runoff (NGW). 0
```

```

12851_Storm Model.out
Number of Interface locations for all Blocks (NIE)..      21
Number of Pumps in Extran (NEP).....                  0
Number of Orifices in Extran (NEO).....                 1
Number of Tide Gates/Free Outfalls in Extran (NTG)..     1
Number of Extran Weirs (NEW).....                       0
Number of scs hydrograph points.....                   1729
Number of Extran printout locations (NPO).....           0
Number of Tide elements in Extran (NTE).....             1
Number of Natural channels (NNC).....                   0
Number of Storage junctions in Extran (NVSE).....         1
Number of Time history data points in Extran(NTVAL)..    0
Number of Variable storage elements in Extran (NVST)     21
Number of Input Hydrographs in Extran (NEH).....         0
Number of Particle sizes in Transport Block (NPS)...     0
Number of User defined conduits (NHW).....              12
Number of Connecting conduits in Extran (NECC).....      20
Number of Upstream elements in Transport (NTCC).....     10
Number of Storage/treatment plants (NSTU).....           1
Number of Values for R1 lines in Transport (NR1).....    0
Number of Nodes to be allowed for (NNOD).....           21
Number of Plugs in a Storage Treatment Unit.....         1

```

```

#####
#      Entry made to the Runoff Layer(Block) of SWMM      #
#      Last Updated January,2009 by XP Software           #

```

```

*=====
|      RUNOFF TABLES IN THE OUTPUT FILE.
|      These are the more important tables in the output file.
|      You can use your editor to find the table numbers,
|      for example: search for Table R3 to check continuity.
|      This output file can be imported into a Word Processor
|      and printed on US letter or A4 paper using portrait
|      mode, courier font, a size of 8 pt. and margins of 0.75
|
|      Table R1 - Physical Hydrology Data
|      Table R2 - Infiltration data
|      Table R3 - Raingage and Infiltration Database Names
|      Table R4 - Groundwater Data
|      Table R5 - Continuity Check for Surface water
|      Table R6 - Continuity Check for Channels/Pipes
|      Table R7 - Continuity Check for Subsurface water
|      Table R8 - Infiltration/Inflow Continuity Check
|      Table R9 - Summary Statistics for Subcatchments
|      Table R10 - Sensitivity anlysis for Subcatchments
|
*=====

```

Red Deer Base

```

#####
#      RUNOFF JOB CONTROL      #
#####

```

```

Snowmelt parameter - ISNOW.....                      0
Number of rain gages - NRGAG.....                     1
Quality is not simulated - KWALTY.....                 0
Default evaporation rate used - IVAP.....              0
Hour of day at start of storm - NHR.....               0
Minute of hour at start of storm - NMN.....            0
Time TZERO at start of storm (hours).....              0.000

```

```

12851_Storm Model.out
Use Metric units for I/O - METRIC..... 1
==> Ft-sec units used in all internal computations
Runoff input print control... 0
Runoff graph plot control.... 1
Runoff output print control.. 0
Limit number of groundwater convergence messages to 10000

Print headers every 50 lines - NOHEAD (0=yes, 1=no) 0

Print land use load percentages -LANDUPR (0=no, 1=yes) 0
Month, day, year of start of storm is: 9/24/2007
Wet time step length (seconds)..... 60.0
Dry time step length (seconds)..... 86400.0
Wet/Dry time step length (seconds)... 60.0
Simulation length is..... 24.0 Hours

```

```

If Horton infiltration model is being used
A mixture of infiltration options may be used in
XP-SWMM2000 as a watershed specific option.
Rate for regeneration of infiltration = REGEN * DECAY
Decay is read in for each subcatchment
REGEN = ..... 0.01000

```

```

Raingage #..... 1
KTYPE - Rainfall input type..... 0
NHISTO - Total number of rainfall values.. 288
KINC - Rainfall values(pairs) per line.. 10
KPRINT - Print rainfall(0-Yes,1-No)..... 0
KTIME - Precipitation time units
0 --> Minutes 1 --> Hours..... 0
KPREP - Precipitation unit type
0 --> Intensity 1 --> Volume..... 0
KTHIS - Variable rainfall intervals
0 --> No, > 1 --> Yes..... 0
THISTO - Rainfall time interval..... 5.00
TZRAIN - Starting time(KTIME units)..... 0.00

```

```

#####
# Rainfall input summary from Runoff #
#####

```

Total rainfall for gage # 1 is 110.1133 mm

```

#####
# Data Group F1 #
# Evaporation Rate (mm/day) #
#####

```

JAN.	FEB.	MAR.	APR.	MAY	JUN.	JUL.	AUG.	SEP.	OCT.	NOV	DEC.
3.000	3.000	3.000	3.000	3.000	3.000	3.000	3.000	3.000	3.000	3.000	3.000

```

#####
# Table R1. S U B C A T C H M E N T D A T A #
# Physical Hydrology Data #
#####

```

Deprs Deprs Prcnt

Per-

12851_Storm Model.out

-sion	-sion	Zero		Channel	width	Area	cent	slope	"n"
"n"	Subcatchment	Storge	Storge	or inlet	(m)	(Ha)	Imperv	ft/ft	Imprv
Number	Storge	Storge	Name						
Perv	Imprv	Perv	-tion						
=====	=====	=====	=====	=====	=====	=====	=====	=====	=====
1			MH 1a#1	MH 1a	125.00	1.3940	70.80	0.001	0.016
0.250	1.600	3.200	0.00	MH 1b	177.63	1.9560	72.90	0.001	0.016
2			MH 1b#1						
0.250	1.600	3.200	0.00	MH 1d	77.726	.84700	71.40	0.014	0.016
3			MH 1d#1						
0.250	1.600	3.200	0.00	MH 1h	98.070	.81200	76.70	0.023	0.016
4			MH 1h#1						
0.250	1.600	3.200	0.00	MH 2	154.35	1.2810	77.30	0.006	0.016
5			MH 2#1						
0.250	1.600	3.200	0.00	MH 3d	164.24	2.2240	75.90	0.009	0.016
6			MH 3d#1						
0.250	1.600	3.200	0.00	MH 3e	123.23	1.4720	76.80	0.001	0.016
7			MH 3e#1						
0.250	1.600	3.200	0.00	MH 1e	121.02	1.1870	74.50	0.006	0.016
8			MH 1e#1						
0.250	1.600	3.200	0.00	MH 1f	176.71	1.7320	77.70	0.004	0.016
9			MH 1f#1						
0.250	1.600	3.200	0.00	MH 3a	172.96	1.4330	74.70	0.003	0.016
10			MH 3a#1						
0.250	1.600	3.200	0.00	MH 3b	114.61	1.3730	77.50	0.002	0.016
11			MH 3b#1						
0.250	1.600	3.200	0.00	MH 4b	61.990	.59800	74.50	0.022	0.016
12			MH 4b#1						
0.250	1.600	3.200	0.00						

#####

Table R2. SUBCATCHMENT DATA

Infiltration or Time of Concentration Data

Infiltration Type Infil #1(#5) Infil #2(#6) Infil #3(#7)
Infil #4(#8) #
SCS -> Comp CN Time Conc Shape Factor
Depth or Fraction #
SBUH -> Comp CN Time Conc N/A
N/A #
Green Ampt -> Suction Hydr Cond Initial MD
N/A #
Horton -> Max Rate Min Rate Decay Rate (1/sec)
Max. Infilt. Volume #
Proportional -> Constant N/A N/A
N/A #
Initial/Cont Loss -> Initial Continuing N/A
N/A #
Initial/Proportional -> Initial Constant N/A
N/A #
Laurenson Parameters -> B Value Pervious "n" Impervious Cont
Exponent #
Rational Formula -> Tc Method Flow Path Length Flow Path Slope
Roughness or Retardance #

Data)

(#1 - #4 is Impervious Data / #5 - #8 is Pervious

```

# Rational Formula Tc Method: 1 = Constant
#                                     2 = Friend's Equation
#                                     3 = Kinematic Wave
#                                     4 = Alameda Method
#                                     5 = Izzard's Formula
#                                     6 = Kerby's Equation
#                                     7 = Kirpich's Equation
#                                     8 = Bransby Williams Equation
#                                     9 = Federal Aviation Authority
# Equation #
#####
#####

```

Subcatchment Infl Number # 7	Infl Name # 8	Infl # 1	Infl # 2	Infl # 3	Infl # 4	Infl # 5	Infl # 6
1	MH 1a#1	75.0000	7.5000	0.0011	0.0000		
2	MH 1b#1	75.0000	7.5000	0.0011	0.0000		
3	MH 1d#1	75.0000	7.5000	0.0011	0.0000		
4	MH 1h#1	75.0000	7.5000	0.0011	0.0000		
5	MH 2#1	75.0000	7.5000	0.0011	0.0000		
6	MH 3d#1	75.0000	7.5000	0.0011	0.0000		
7	MH 3e#1	75.0000	7.5000	0.0011	0.0000		
8	MH 1e#1	75.0000	7.5000	0.0011	0.0000		
9	MH 1f#1	75.0000	7.5000	0.0011	0.0000		
10	MH 3a#1	75.0000	7.5000	0.0011	0.0000		
11	MH 3b#1	75.0000	7.5000	0.0011	0.0000		
12	MH 4b#1	75.0000	7.5000	0.0011	0.0000		

```

#####
# Table R3. SUBCATCHMENT DATA #
# Rainfall and Infiltration Database Names #
#####

```

Subcatchment Infiltration Number Name	Gage Infiltration No Type	Routing Type	Rainfall Database
Database Name			

12851_Storm Model.out

```
=====
1      MH 1a#1      1      Horton Non-linear reservoir
2      MH 1b#1      1      Horton Non-linear reservoir
3      MH 1d#1      1      Horton Non-linear reservoir
4      MH 1h#1      1      Horton Non-linear reservoir
5      MH 2#1       1      Horton Non-linear reservoir
6      MH 3d#1      1      Horton Non-linear reservoir
7      MH 3e#1      1      Horton Non-linear reservoir
8      MH 1e#1      1      Horton Non-linear reservoir
9      MH 1f#1      1      Horton Non-linear reservoir
10     MH 3a#1      1      Horton Non-linear reservoir
11     MH 3b#1      1      Horton Non-linear reservoir
12     MH 4b#1      1      Horton Non-linear reservoir
```

```
Total Number of Subcatchments...      12
Total Tributary Area (hectares).      16.31
Impervious Area (hectares).....      12.26
Pervious Area (hectares).....         4.05
Total Width (metres).....      1567.53
Impervious Area (%).....      75.17
```

```
#####
#      S U B C A T C H M E N T   D A T A      #
#      Default, Ratio values for subcatchment data #
#      Used with the calibrate node in the runoff. #
# 1 - width      2 - area      3 - impervious %      #
# 4 - slope      5 - imp "n"    6 - perv "n"      #
# 7 - imp ds      8 - perv ds    9 - 1st infil      #
#10 - 2nd infil      11 - 3rd infil      #
#####
```

Column	1	2	3	4	5	6	7
8	9	10	11				
Default	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Ratio	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000

```
*****
*      Arrangement of Subcatchments and Channel/Pipes      *
*****
```

```
Inlet
MH 1a      No Tributary Channel/Pipes
            Tributary Subareas..... MH 1a#1
MH 1b      No Tributary Channel/Pipes
            Tributary Subareas..... MH 1b#1
MH 1d      No Tributary Channel/Pipes
            Tributary Subareas..... MH 1d#1
MH 1h      No Tributary Channel/Pipes
            Tributary Subareas..... MH 1h#1
MH 2       No Tributary Channel/Pipes
            Tributary Subareas..... MH 2#1
MH 3d      No Tributary Channel/Pipes
            Tributary Subareas..... MH 3d#1
MH 3e      No Tributary Channel/Pipes
            Tributary Subareas..... MH 3e#1
MH 1e      No Tributary Channel/Pipes
            Tributary Subareas..... MH 1e#1
MH 1f      No Tributary Channel/Pipes
            Tributary Subareas..... MH 1f#1
```

12851_Storm Model.out

MH 3a No Tributary Channel/Pipes
 Tributary Subareas..... MH 3a#1
 MH 3b No Tributary Channel/Pipes
 Tributary Subareas..... MH 3b#1
 MH 4b No Tributary Channel/Pipes
 Tributary Subareas..... MH 4b#1

 * Hydrographs will be stored for the following 12 INLETS *

MH 1a MH 1b MH 1d MH 1h MH 2 MH 3d
 MH 3e MH 1e MH 1f MH 3a MH 3b MH 4b

 * Quality Simulation not included in this run *

 * Precipitation Interface File Summary *
 * Number of precipitation station.... 1 *

Location Station Number

 1. 1

 * End of time step DO-loop in Runoff *

Final Date (Mo/Day/Year) = 9/25/2007
 Total number of time steps = 1440
 Final Julian Date = 2007268
 Final time of day = 0. seconds.
 Final time of day = 0.00 hours.
 Final running time = 24.0000 hours.
 Final running time = 1.0000 days.

 * Extrapolation Summary for Watersheds *
 * Explains the number of time steps and iterations *
 * used in the solution of the subcatchments. *
 * # Steps ==> Total Number of Extrapolated Steps *
 * # Calls ==> Total Number of OVERLND Calls *

Subcatchment	# Steps	# Calls	Subcatchment	# Steps	# Calls
MH 1a#1	4905	1627	MH 1b#1	4885	1619
5728	1560				
MH 1h#1	8411	1537	MH 2#1	5211	1557
4966	1570				
MH 3e#1	4857	1615	MH 1e#1	5072	1568
4906	1570				
MH 3a#1	4949	1575	MH 3b#1	4840	1596
7136	1544				

12851_Storm Model.out

 # Rainfall input summary from Runoff Continuity Check #
 #####

Total rainfall read for gage # 1 is 110.11 mm
 Total rainfall duration for gage # 1 is 1440.00 minutes

 * Table R5. CONTINUITY CHECK FOR SURFACE WATER *
 * Any continuity error can be fixed by lowering the *
 * wet and transition time step. The transition time *
 * should not be much greater than the wet time step. *

		Millimeters
over		
	cubic meters	Total Basin
Total Precipitation (Rain plus Snow)	1.795838E+04	110.113
Total Infiltration	3.864181E+03	23.694
Total Evaporation	4.892784E+02	3.000
Surface Runoff from Watersheds	1.326310E+04	81.324
Total Water remaining in Surface Storage	3.454069E+02	2.118
Infiltration over the Pervious Area...	3.864181E+03	95.418

Infiltration + Evaporation +		
Surface Runoff + Snow removal +		
Water remaining in Surface Storage +		
Water remaining in Snow Cover.....	1.796196E+04	110.135
Total Precipitation + Initial Storage.	1.795838E+04	110.113

The error in continuity is calculated as

 * Precipitation + Initial Snow Cover *
 * - Infiltration - *
 *Evaporation - Snow removal - *
 *Surface Runoff from Watersheds - *
 *Water in Surface Storage - *
 *Water remaining in Snow Cover *

 * Precipitation + Initial Snow Cover *

 Percent Continuity Error.....

-0.0199

 * Table R6. Continuity Check for Channel/Pipes *
 * You should have zero continuity error *
 * if you are not using runoff hydraulics *

		Millimeters
over		
	cubic meters	Total Basin
Initial Channel/Pipe Storage.....	0.000000E+00	0.000
Final Channel/Pipe Storage.....	0.000000E+00	0.000
Surface Runoff from Watersheds.....	1.326310E+04	81.324
Groundwater Subsurface Inflow or Diversion..	0.000000E+00	0.000
Evaporation Loss from Channels.....	0.000000E+00	0.000
Groundwater Flow Diverted Out of Network....	0.000000E+00	0.000
Channel/Pipe/Inlet Outflow.....	1.326310E+04	81.324
Initial Storage + Inflow.....	1.326310E+04	81.324
Final Storage + Outflow + Diverted GW.....	1.326310E+04	81.324

12851_Storm Model.out

```
* Final Storage + Outflow + Evaporation - *
* Watershed Runoff - Groundwater Inflow - *
* Initial Channel/Pipe Storage *
* ----- *
* Final Storage + Outflow + Evaporation *
*****
```

Percent Continuity Error..... 0.0000

```
#####
# Table R9. Summary Statistics for Subcatchments #
#####
```

Note: Total Runoff Depth includes pervious & impervious areas.
Pervious and Impervious Runoff Depth is only the runoff from those two areas.
Subcatchments #1*, #2*, #3*, #4* and #5* are the fractions of Subcatchments
#1, #2, #3, #4 and #5,
respectively, those have been redirected to another Subcatchment.

Subcatchment.....	MH 1a#1	MH 1b#1	MH 1d#1
MH 1h#1 MH 2#1	MH 3d#1		
Area (hectares).....	1.39403	1.95604	0.84702
0.81202 1.28103	2.22405		
Percent Impervious.....	70.80000	72.90000	71.40000
76.70000 77.30000	75.90000		
Total Rainfall (mm)....	110.11333	110.11333	110.11333
110.11333 110.11333	110.11333		
Max Intensity (mm/hr)..	100.18000	100.18000	100.18000
100.18000 100.18000	100.18000		

Pervious Area

Total Runoff Depth (mm)	9.90109	10.27336	12.67575
13.34154 12.76930	12.31868		
Peak Runoff Rate (cms).	0.00660	0.00947	0.01035
0.01478 0.01315	0.01896		

Total Impervious Area

Total Runoff Depth (mm)	103.79403	103.83187	104.79223
104.97698 104.67747	104.52279		
Peak Runoff Rate (cms).	0.13714	0.20129	0.13708
0.15502 0.21108	0.33129		

Impervious Area with depression storage

Total Runoff Depth (mm)	103.79403	103.83187	104.79223
104.97698 104.67747	104.52279		
Peak Runoff Rate (cms).	0.13714	0.20129	0.13708
0.15502 0.21108	0.33129		

Impervious Area without depression storage

Total Runoff Depth (mm)	0.00000	0.00000	0.00000
0.00000 0.00000	0.00000		
Peak Runoff Rate (cms).	0.00000	0.00000	0.00000
0.00000 0.00000	0.00000		

Total Area

Total Runoff Depth (mm)	76.37729	78.47751	78.44691
83.62593 83.81431	82.30160		
Peak Runoff Rate (cms).	0.14166	0.20803	0.14729

0.16981	0.22423	12851_Storm Model.out	
		0.34902	
Rational Formula			

Pervious Tc. (mins)....		0.00000	0.00000
0.00000	0.00000	0.00000	0.00000
Perv. Intensity (mm/hr)		0.00000	0.00000
0.00000	0.00000	0.00000	0.00000
Pervious C		0.00000	0.00000
0.00000	0.00000	0.00000	0.00000
Impervious Tc. (mins)..		0.00000	0.00000
0.00000	0.00000	0.00000	0.00000
Imp. Intensity (mm/hr).		0.00000	0.00000
0.00000	0.00000	0.00000	0.00000
Impervious C		0.00000	0.00000
0.00000	0.00000	0.00000	0.00000
Partial Area (Ha).....		0.00000	0.00000
0.00000	0.00000	0.00000	0.00000
Partial Area Tc.....		0.00000	0.00000
0.00000	0.00000	0.00000	0.00000
Partial Area Intensity.		0.00000	0.00000
0.00000	0.00000	0.00000	0.00000
Subcatchment.....		MH 3e#1	MH 1e#1
MH 3a#1	MH 3b#1	MH 4b#1	MH 1f#1
Area (hectares).....		1.47203	1.73204
1.43303	1.37303	0.59801	
Percent Impervious.....		76.80000	74.50000
74.70000	77.50000	74.50000	77.70000
Total Rainfall (mm)....		110.11333	110.11333
110.11333	110.11333	110.11333	110.11333
Max Intensity (mm/hr)..		100.18000	100.18000
100.18000	100.18000	100.18000	100.18000
Pervious Area			

Total Runoff Depth (mm)		10.46203	12.40977
12.15592	11.32337	13.14403	12.31184
Peak Runoff Rate (cms).		0.00642	0.01122
0.01185	0.00746	0.00959	0.01362
Total Impervious Area			

Total Runoff Depth (mm)		103.68772	104.60556
104.49624	104.02822	104.92238	104.45487
Peak Runoff Rate (cms).		0.15043	0.18137
0.20716	0.16366	0.10800	0.25487
Impervious Area with depression storage			

Total Runoff Depth (mm)		103.68772	104.60556
104.49624	104.02822	104.92238	104.45487
Peak Runoff Rate (cms).		0.15043	0.18137
0.20716	0.16366	0.10800	0.25487
Impervious Area without depression storage			

Total Runoff Depth (mm)		0.00000	0.00000
0.00000	0.00000	0.00000	0.00000
Peak Runoff Rate (cms).		0.00000	0.00000
0.00000	0.00000	0.00000	0.00000

120.000 =		
		=
RAINFALL		
IN		
#		
#		
MM/HR		
#		
#		
#		
80.000 =		
#		=
#		
#		
#		
#		
#		
#		
#		
#		
#		
40.000 =		
#		=
#		
#		
##		
###		
# ##		
## ###		
#### #####		

#####

##

#

0.000

#=====|=====|=====|=====|=====|=====|=====|=====|=#

=====|=====|

7.0 8.0 0.0 9.0 1.0 10.0 2.0 3.0 4.0 5.0 6.0

LOCATION NO. : 1

TIME IN HOURS

[illegible]

[illegible]

Page 16

1.600 = #

#

$$= \#$$

| #

| #

| #

| #

| #

| #

| #

| #

| #

$$= \#$$

0.800 = #

| #

| #

| #

| #

| #

| #

| #

| #

| #

0.000

01989

|==#==|==||==||==||==||==||==
=====|#

21.6 22.4 23.2 24.0 16.0 16.8 17.6 18.4 19.2 20.0 20.8

LOCATION NO. : 1

TIME IN HOURS

RAINFALL HYETOGRAPH

RANGE AND SCALE ARE ZERO ON PLOT ATTEMPT FOR LOCATION: FLOW SUM

RANGE AND SCALE ARE ZERO ON PLOT ATTEMPT FOR LOCATION: INFILTRA

```
====> Runoff simulation ended normally.
```

```
#####
#      Entry made to the HYDRAULIC Layer(Block) of SWMM #
#      Last Updated in January, 2009 by XP Software     #
#####
```

Red Deer Base

```

=====
HYDRAULICS TABLES IN THE OUTPUT FILE
These are the more important tables in the output file.
You can use your editor to find the table numbers,
for example: search for Table E20 to check continuity.
This output file can be imported into a Word Processor
and printed on US letter or A4 paper using portrait
mode, courier font, a size of 8 pt. and margins of 0.75

Table E1  - Basic Conduit Data
Table E2  - Conduit Factor Data
Table E3a - Junction Data
Table E3b - Junction Data
Table E4  - Conduit Connectivity Data
Table E4a - Dry Weather Flow Data
Table E4b - Real Time Control Data
Table E5  - Junction Time Step Limitation Summary
Table E5a - Conduit Explicit Condition Summary
Table E6  - Final Model Condition
Table E7  - Iteration Summary
Table E8  - Junction Time Step Limitation Summary
Table E9  - Junction Summary Statistics
Table E10 - Conduit Summary Statistics
Table E11 - Area assumptions used in the analysis
Table E12 - Mean conduit information
Table E13 - Channel losses(H) and culvert info
Table E13a - Culvert Analysis Classification
Table E14 - Natural Channel Overbank Flow Information
Table E14a - Natural Channel Encroachment Information
Table E14b - Floodplain Mapping
Table E15 - Spreadsheet Info List
Table E15a - Spreadsheet Reach List
Table E16 - New Conduit Output Section
Table E17 - Pump Operation
Table E18 - Junction Continuity Error
Table E19 - Junction Inflow & Outflow Listing
Table E20 - Junction Flooding and Volume List
Table E21 - Continuity balance at simulation end
Table E22 - Model Judgement Section
=====

```

Time Control from Hydraulics Job Control

Year.....	2007	Month.....	9
Day.....	24	Hour.....	0
Minute.....	0	Second.....	0

Control information for simulation

Integration cycles.....	2880
Length of integration step is.....	30.00 seconds
Simulation length.....	24.00 hours
Do not create equiv. pipes(NEQUAL).	0
Use metric units for I/O.....	1
Printing starts in cycle.....	1

```

12851_Storm Model.out
Intermediate printout intervals of.      500 cycles
Intermediate printout intervals of.      250.00 minutes
Summary printout intervals of.....      500 cycles
Summary printout time interval of..      250.00 minutes
Hot start file parameter (REDO)....      0
Initial time.....      0.00 hours

Iteration variables: Flow Tolerance.      0.00010
                      Head Tolerance.      0.00005
                      Minimum depth (m or ft)..... 0.00001
                      Underrelaxation parameter..... 0.85000
                      Time weighting parameter..... 0.85000
                      Conduit roughness factor..... 1.00000
                      Flow adjustment factor..... 1.00000
                      Initial Condition Smoothing..... 0
                      Courant Time Step Factor..... 1.00000
                      Default Expansion/Contraction K. 0.00000
                      Default Entrance/Exit K..... 0.00000
                      Routing Method..... Dynamic wave
                      Default surface area of junctions... 1.22 square meters.
                      Minimum Junction/Conduit Depth..... 0.00001 meter.
                      Ponding Area Coefficient..... 5000.00
                      Ponding Area Exponent..... 1.0000
                      Minimum Orifice Length..... 1.00 meters.
NJSW input hydrograph junctions..... 0
or user defined hydrographs....

```

```

*=====*
| Table E1 - Conduit Data |
*=====*

```

Inp Depth Num (m)	Trapezoid Conduit Side slopes	Conduit Name	Length (m)	Conduit Class	Area (m^2)	Manning Coef.	Max width (m)
1		P4a-4c	16.1110	Circular	1.7671	0.0130	1.5000
1.5000							
2		P3f-4a	35.4150	Trapezoid	1.4200	0.0130	2.3500
0.4000	3.0000	3.0000					
3		P3e-3f	119.2310	Trapezoid	1.0400	0.0130	1.0000
0.4000	3.0000	5.0000					
4		P3d-3e	172.2360	Trapezoid	1.0400	0.0130	1.0000
0.4000	3.0000	5.0000					
5		P3c-3f	16.3990	Circular	1.4314	0.0130	1.3500
1.3500							
6		P2-4c	154.2870	Trapezoid	1.0400	0.0130	1.0000
0.4000	3.0000	5.0000					
7		P1h-2	89.7280	Trapezoid	1.0400	0.0130	1.0000
0.4000	3.0000	5.0000					
8		P1g-3c	192.5690	Trapezoid	1.0400	0.0130	1.0000
0.4000	3.0000	5.0000					
9		P1f-1g	168.3010	Trapezoid	1.0400	0.0130	1.0000
0.4000	3.0000	5.0000					
10		P1e-1f	120.9960	Trapezoid	1.0400	0.0130	1.0000
0.4000	3.0000	5.0000					
11		P1c-1h	16.6120	Circular	0.6362	0.0130	0.9000
0.9000							
12		P1b-1c	181.0080	Trapezoid	1.0400	0.0130	1.0000
0.4000	3.0000	5.0000					

12851_Storm Model.out						
13	P1a-1b	125.1050	Trapezoid	1.0400	0.0130	1.0000
0.4000	3.0000	5.0000				
14	P3b-3c	116.7390	Trapezoid	1.0400	0.0130	1.0000
0.4000	3.0000	5.0000				
15	P3a-3b	175.0930	Trapezoid	1.0400	0.0130	1.0000
0.4000	3.0000	5.0000				
16	P4c-4d	75.0300	Trapezoid	1.2800	0.0130	2.0000
0.4000	3.0000	3.0000				
17	P1d-1c	74.3500	Trapezoid	1.0400	0.0130	1.0000
0.4000	3.0000	5.0000				
18	P4b-4c	61.7880	Trapezoid	1.0400	0.0130	1.0000
0.4000	3.0000	5.0000				
19	Link25	10.0000	Circular	3.1416	0.0140	2.0000
2.0000						
Total length of all conduits				1920.9980 meters		

```

*=====
| If there are messages about (sqrt(g*d)*dt/dx), or
| the sqrt(wave celerity)*time step/conduit length
| in the output file all it means is that the
| program will lower the internal time step to
| satisfy this condition (explicit condition).
| You control the actual internal time step by
| using the minimum courant time step factor in the
| HYDRAULICS job control. The message put in words
| states that the smallest conduit with the fastest
| velocity will control the time step selection.
| You have further control by using the modify
| conduit option in the HYDRAULICS Job Control.
*=====

```

Conduit Name	Courant Ratio	
P4a-4c	7.14	====> warning ! (sqrt(wave celerity)*time step/conduit length)
P3f-4a	1.45	====> warning ! (sqrt(wave celerity)*time step/conduit length)
P3e-3f	0.39	
P3d-3e	0.27	
P3c-3f	6.66	====> warning ! (sqrt(wave celerity)*time step/conduit length)
P2-4c	0.30	
P1h-2	0.52	
P1g-3c	0.24	
P1f-1g	0.28	
P1e-1f	0.39	
P1c-1h	5.36	====> warning ! (sqrt(wave celerity)*time step/conduit length)
P1b-1c	0.26	
P1a-1b	0.37	
P3b-3c	0.40	
P3a-3b	0.27	
P4c-4d	0.68	
P1d-1c	0.63	
P4b-4c	0.76	
Link25	13.29	====> warning ! (sqrt(wave celerity)*time step/conduit length)

```

*=====
| Conduit Volume |
*=====

```

12851_Storm Model.out

Full pipe or full open conduit volume

Input full depth volume..... 2.0617E+03 cubic meters

=====

| Table E3a - Junction Data |

=====

Inp Num	Junction Name	Ground Elevation	Crown Elevation	Invert Elevation	Qinst cms	Initial Depth-m	Interface Flow (%)
1	MH 1a	938.9150	938.9150	938.5150	0.0000	0.0000	100.0000
2	MH 1e	938.9140	938.9140	938.5140	0.0000	0.0000	100.0000
3	MH 1f	938.1880	938.1880	937.7720	0.0000	0.0000	100.0000
4	MH 1b	938.1780	938.1780	937.7780	0.0000	0.0000	100.0000
5	MH 1d	937.6230	937.6230	937.2230	0.0000	0.0000	100.0000
6	MH 1c	937.4700	937.3140	936.4140	0.0000	0.0000	100.0000
7	MH 1g	937.1620	937.1620	936.5100	0.0000	0.0000	100.0000
8	MH 1h	937.2500	936.9620	936.0620	0.0000	0.0000	100.0000
9	MH 3a	935.7190	935.7190	935.3190	0.0000	0.0000	100.0000
10	MH 3d	935.6950	935.6950	935.2950	0.0000	0.0000	100.0000
11	MH 2	935.1400	935.1400	934.4470	0.0000	0.0000	100.0000
12	MH 3b	934.6770	934.6770	934.2770	0.0000	0.0000	100.0000
13	MH 3e	934.6610	934.6610	934.2610	0.0000	0.0000	100.0000
14	MH 4b	934.0260	934.0260	933.6260	0.0000	0.0000	100.0000
15	MH 3f	933.9510	933.9510	932.5190	0.0000	0.0000	100.0000
16	MH 3c	934.2600	934.0270	932.6590	0.0000	0.0000	100.0000
17	MH 4a	933.9500	933.8170	932.3120	0.0000	0.0000	100.0000
18	MH 4c	933.9500	933.7360	932.2360	0.0000	0.0000	100.0000
19	MH 4d	932.6000	932.4220	930.5000	0.0000	0.0000	100.0000
20	orifice	932.6000	932.5000	930.5000	0.0000	0.0000	100.0000
21	Node22	932.0000	927.5000	925.5000	0.0000	0.0000	100.0000

=====

| Table E3b - Junction Data |

=====

Inp Num	Junction Pavement Name	X Coord.	Y Coord.	Type of Manhole	Type of Inlet	Maximum Capacity
------------	------------------------------	-------------	-------------	--------------------	------------------	---------------------

12851_Storm Model.out

Shape	Slope					
1	0	MH 1a	0.0000	0.0000	No P	Normal
2	0	MH 1e	0.0000	0.0000	No P	Normal
3	0	MH 1f	0.0000	0.0000	No P	Normal
4	0	MH 1b	0.0000	0.0000	No P	Normal
5	0	MH 1d	0.0000	0.0000	No P	Normal
6	0	MH 1c	0.0000	0.0000	No P	Normal
7	0	MH 1g	0.0000	0.0000	No P	Normal
8	0	MH 1h	0.0000	0.0000	No P	Normal
9	0	MH 3a	0.0000	0.0000	No P	Normal
10	0	MH 3d	0.0000	0.0000	No P	Normal
11	0	MH 2	0.0000	0.0000	No P	Normal
12	0	MH 3b	0.0000	0.0000	No P	Normal
13	0	MH 3e	0.0000	0.0000	No P	Normal
14	0	MH 4b	0.0000	0.0000	No P	Normal
15	0	MH 3f	0.0000	0.0000	No P	Normal
16	0	MH 3c	0.0000	0.0000	No P	Normal
17	0	MH 4a	0.0000	0.0000	No P	Normal
18	0	MH 4c	0.0000	0.0000	No P	Normal
19	0	MH 4d	0.0000	0.0000	No P	Normal
20	0	Orifice	0.0000	0.0000	No P	Normal
21	0	Node22	0.0000	0.0000	No P	Normal

=====

| Table E4 - Conduit Connectivity |

=====

Input Number	Conduit Name	Upstream Node	Downstream Node	Upstream Elevation	Downstream Elevation
1	P4a-4c	MH 4a	MH 4c	932.3170	932.2360
No Design					
2	P3f-4a	MH 3f	MH 4a	932.5240	932.3120
No Design					
3	P3e-3f	MH 3e	MH 3f	934.2610	933.5510
No Design					
4	P3d-3e	MH 3d	MH 3e	935.2950	934.2610
No Design					
5	P3c-3f	MH 3c	MH 3f	932.6770	932.5190

12851_Storm Model.out

No Design 6	P2-4c	MH 2	MH 4c	934.4470	932.4410
No Design 7	P1h-2	MH 1h	MH 2	936.0810	934.7400
No Design 8	P1g-3c	MH 1g	MH 3c	936.5100	932.6590
No Design 9	P1f-1g	MH 1f	MH 1g	937.7720	936.7620
No Design 10	P1e-1f	MH 1e	MH 1f	938.5140	937.7880
No Design 11	P1c-1h	MH 1c	MH 1h	936.4140	936.0620
No Design 12	P1b-1c	MH 1b	MH 1c	937.7780	936.7880
No Design 13	P1a-1b	MH 1a	MH 1b	938.5150	937.7780
No Design 14	P3b-3c	MH 3b	MH 3c	934.2770	933.5730
No Design 15	P3a-3b	MH 3a	MH 3b	935.3190	934.2770
No Design 16	P4c-4d	MH 4c	MH 4d	932.2410	932.0220
No Design 17	P1d-1c	MH 1d	MH 1c	937.2230	936.6900
No Design 18	P4b-4c	MH 4b	MH 4c	933.6260	933.2660
No Design 19	Link25	Orifice	Node22	930.5000	925.5000

=====

Storage Junction Data

=====

STORAGE JUNCTION NUMBER OR NAME	JUNCTION TYPE	MAXIMUM OR CONSTANT SURFACE AREA (M2)	PEAK OR CONSTANT VOLUME (CUBIC MET.)	CROWN ELEVATION (M)	DEPTH STARTS FROM
-----	-----	-----	-----	-----	-----
Invert	MH 4d Stage/Area	10720.5400	17987.4015	932.6000	Node

=====

Variable storage data for node MH 4d

=====

Data Point	Elevation meters	Depth meters	Area m^2	Volume m^3
=====	=====	=====	=====	=====
1	930.5000	0.0000	2533.1200	0.0000
2	930.5125	0.0125	3031.3950	34.7316
3	930.5250	0.0250	3529.6700	75.6988
4	930.5375	0.0375	4027.9450	122.8997
5	930.5500	0.0500	4526.2200	176.3329
6	930.5625	0.0625	5024.4950	235.9978
7	930.5750	0.0750	5522.7700	301.8937

8	930.5875	0.0875	12851_Storm Model.out 6021.0450	374.0201
9	930.6000	0.1000	6519.3200	452.3768
10	930.6125	0.1125	6546.8312	534.0401
11	930.6250	0.1250	6574.3425	616.0474
12	930.6375	0.1375	6601.8537	698.3986
13	930.6500	0.1500	6629.3650	781.0936
14	930.6625	0.1625	6656.8763	864.1326
15	930.6750	0.1750	6684.3875	947.5154
16	930.6875	0.1875	6711.8988	1031.2422
17	930.7000	0.2000	6739.4100	1115.3128
18	930.7125	0.2125	6767.1175	1199.7285
19	930.7250	0.2250	6794.8250	1284.4906
20	930.7375	0.2375	6822.5325	1369.5990
21	930.7500	0.2500	6850.2400	1455.0538
22	930.7625	0.2625	6877.9475	1540.8549
23	930.7750	0.2750	6905.6550	1627.0024
24	930.7875	0.2875	6933.3625	1713.4962
25	930.8000	0.3000	6961.0700	1800.3363
26	930.8125	0.3125	6988.9725	1887.5240
27	930.8250	0.3250	7016.8750	1975.0605
28	930.8375	0.3375	7044.7775	2062.9458
29	930.8500	0.3500	7072.6800	2151.1798
30	930.8625	0.3625	7100.5825	2239.7627
31	930.8750	0.3750	7128.4850	2328.6943
32	930.8875	0.3875	7156.3875	2417.9747
33	930.9000	0.4000	7184.2900	2507.6039
34	930.9125	0.4125	7212.3887	2597.5830
35	930.9250	0.4250	7240.4875	2687.9135
36	930.9375	0.4375	7268.5862	2778.5951
37	930.9500	0.4500	7296.6850	2869.6280
38	930.9625	0.4625	7324.7838	2961.0121
39	930.9750	0.4750	7352.8825	3052.7475

12851_Storm Model.out

40	930.9875	0.4875	7380.9813	3144.8341
41	931.0000	0.5000	7409.0800	3237.2719
42	931.0125	0.5125	7437.3750	3330.0622
43	931.0250	0.5250	7465.6700	3423.2062
44	931.0375	0.5375	7493.9650	3516.7038
45	931.0500	0.5500	7522.2600	3610.5552
46	931.0625	0.5625	7550.5550	3704.7602
47	931.0750	0.5750	7578.8500	3799.3189
48	931.0875	0.5875	7607.1450	3894.2314
49	931.1000	0.6000	7635.4400	3989.4975
50	931.1125	0.6125	7663.9300	4085.1185
51	931.1250	0.6250	7692.4200	4181.0956
52	931.1375	0.6375	7720.9100	4277.4289
53	931.1500	0.6500	7749.4000	4374.1182
54	931.1625	0.6625	7777.8900	4471.1638
55	931.1750	0.6750	7806.3800	4568.5654
56	931.1875	0.6875	7834.8700	4666.3231
57	931.2000	0.7000	7863.3600	4764.4370
58	931.2125	0.7125	7892.0463	4862.9083
59	931.2250	0.7250	7920.7325	4961.7381
60	931.2375	0.7375	7949.4187	5060.9265
61	931.2500	0.7500	7978.1050	5160.4734
62	931.2625	0.7625	8006.7913	5260.3790
63	931.2750	0.7750	8035.4775	5360.6431
64	931.2875	0.7875	8064.1638	5461.2658
65	931.3000	0.8000	8092.8500	5562.2471
66	931.3125	0.8125	8121.7313	5663.5882
67	931.3250	0.8250	8150.6125	5765.2903
68	931.3375	0.8375	8179.4937	5867.3534
69	931.3500	0.8500	8208.3750	5969.7775
70	931.3625	0.8625	8237.2563	6072.5627

		12851_Storm Model.out		
71	931.3750	0.8750	8266.1375	6175.7088
72	931.3875	0.8875	8295.0187	6279.2160
73	931.4000	0.9000	8323.9000	6383.0842
74	931.4125	0.9125	8352.9775	6487.3146
75	931.4250	0.9250	8382.0550	6591.9085
76	931.4375	0.9375	8411.1325	6696.8659
77	931.4500	0.9500	8440.2100	6802.1867
78	931.4625	0.9625	8469.2875	6907.8710
79	931.4750	0.9750	8498.3650	7013.9188
80	931.4875	0.9875	8527.4425	7120.3300
81	931.5000	1.0000	8556.5200	7227.1048
82	931.5125	1.0125	8585.7925	7334.2442
83	931.5250	1.0250	8615.0650	7441.7495
84	931.5375	1.0375	8644.3375	7549.6207
85	931.5500	1.0500	8673.6100	7657.8578
86	931.5625	1.0625	8702.8825	7766.4608
87	931.5750	1.0750	8732.1550	7875.4298
88	931.5875	1.0875	8761.4275	7984.7646
89	931.6000	1.1000	8790.7000	8094.4653
90	931.6125	1.1125	8820.1688	8204.5332
91	931.6250	1.1250	8849.6375	8314.9695
92	931.6375	1.1375	8879.1063	8425.7741
93	931.6500	1.1500	8908.5750	8536.9470
94	931.6625	1.1625	8938.0438	8648.4883
95	931.6750	1.1750	8967.5125	8760.3980
96	931.6875	1.1875	8996.9813	8872.6760
97	931.7000	1.2000	9026.4500	8985.3224
98	931.7125	1.2125	9056.1150	9098.3384
99	931.7250	1.2250	9085.7800	9211.7252
100	931.7375	1.2375	9115.4450	9325.4828
101	931.7500	1.2500	9145.1100	9439.6112
102	931.7625	1.2625	9174.7750	9554.1105

12851_Storm Model.out

103	931.7750	1.2750	9204.4400	9668.9805
104	931.7875	1.2875	9234.1050	9784.2214
105	931.8000	1.3000	9263.7700	9899.8330
106	931.8125	1.3125	9293.6300	10015.8167
107	931.8250	1.3250	9323.4900	10132.1737
108	931.8375	1.3375	9353.3500	10248.9039
109	931.8500	1.3500	9383.2100	10366.0073
110	931.8625	1.3625	9413.0700	10483.4840
111	931.8750	1.3750	9442.9300	10601.3340
112	931.8875	1.3875	9472.7900	10719.5572
113	931.9000	1.4000	9502.6500	10838.1536
114	931.9125	1.4125	9532.7063	10957.1246
115	931.9250	1.4250	9562.7625	11076.4712
116	931.9375	1.4375	9592.8188	11196.1935
117	931.9500	1.4500	9622.8750	11316.2916
118	931.9625	1.4625	9652.9312	11436.7653
119	931.9750	1.4750	9682.9875	11557.6148
120	931.9875	1.4875	9713.0438	11678.8399
121	932.0000	1.5000	9743.1000	11800.4408
122	932.0125	1.5125	9767.2850	11922.3806
123	932.0250	1.5250	9791.4700	12044.6228
124	932.0375	1.5375	9815.6550	12167.1673
125	932.0500	1.5500	9839.8400	12290.0141
126	932.0625	1.5625	9864.0250	12413.1633
127	932.0750	1.5750	9888.2100	12536.6147
128	932.0875	1.5875	9912.3950	12660.3684
129	932.1000	1.6000	9936.5800	12784.4245
130	932.1125	1.6125	9960.8913	12908.7837
131	932.1250	1.6250	9985.2025	13033.4467
132	932.1375	1.6375	10009.5138	13158.4137
133	932.1500	1.6500	10033.8250	13283.6845

		12851_Storm Model.out		
134	932.1625	1.6625	10058.1362	13409.2592
135	932.1750	1.6750	10082.4475	13535.1379
136	932.1875	1.6875	10106.7588	13661.3204
137	932.2000	1.7000	10131.0700	13787.8068
138	932.2125	1.7125	10155.5062	13914.5978
139	932.2250	1.7250	10179.9425	14041.6944
140	932.2375	1.7375	10204.3787	14169.0963
141	932.2500	1.7500	10228.8150	14296.8038
142	932.2625	1.7625	10253.2512	14424.8166
143	932.2750	1.7750	10277.6875	14553.1350
144	932.2875	1.7875	10302.1238	14681.7588
145	932.3000	1.8000	10326.5600	14810.6880
146	932.3125	1.8125	10351.1213	14939.9235
147	932.3250	1.8250	10375.6825	15069.4660
148	932.3375	1.8375	10400.2437	15199.3155
149	932.3500	1.8500	10424.8050	15329.4720
150	932.3625	1.8625	10449.3663	15459.9356
151	932.3750	1.8750	10473.9275	15590.7061
152	932.3875	1.8875	10498.4888	15721.7837
153	932.4000	1.9000	10523.0500	15853.1683
154	932.4125	1.9125	10547.7363	15984.8607
155	932.4250	1.9250	10572.4225	16116.8616
156	932.4375	1.9375	10597.1087	16249.1712
157	932.4500	1.9500	10621.7950	16381.7893
158	932.4625	1.9625	10646.4813	16514.7160
159	932.4750	1.9750	10671.1675	16647.9513
160	932.4875	1.9875	10695.8538	16781.4951
161	932.5000	2.0000	10720.5400	16915.3475
162	932.6000	2.1000	10720.5400	17987.4015

=====
 | Orifice Data |
 =====

12851_Storm Model.out

Discharge Coefficient	Orifice Height Above Junction (m)	From Junction	To Junction	Type	Area (m2)	Depth (m)
0.600	0.000	MH 4d	orifice	Circ Side	0.03	0.00

```

====> EQUIVALENT PIPE INFORMATION FOR ORIFICE 1
CONDUIT NAME..... orifice_1
Upstream node..... MH 4d
Downstream node..... orifice
PIPE DIAMETER..... 0.19
PIPE LENGTH..... 300.00
MANNINGS ROUGHNESS..... 0.0029
INVERT ELEVATION AT UPSTREAM END..... 930.5000
INVERT ELEVATION AT DOWNSTREAM END... 930.4970
  
```

Note: For a Bottom-outlet orifice the invert elevation of the downstream node will be adjusted to accomodate the equivalent conduit. Conduit grades are not affected.

```

*=====*
|          FREE OUTFALL DATA (DATA GROUP I1)          |
|          BOUNDARY CONDITION ON DATA GROUP J1          |
|=====|
  
```

Outfall at Junction....Node22 has boundary condition number... 1

```

*=====*
|          INTERNAL CONNECTIVITY INFORMATION          |
|=====|
  
```

CONDUIT	JUNCTION	JUNCTION
orifice_1 FREE # 1	MH 4d Node22	orifice BOUNDARY

```

*=====*
|          Boundary Condition Information          |
|          Data Groups J1-J4          |
|=====|
  
```

BC NUMBER.. 1 has no control water surface.

```

#####
# Header information from interface file: #
#####
  
```

Title from first computational layer:
Red Deer Base

Title from immediately preceding computational layer
Red Deer Base

12851_Storm Model.out

Name of preceding layer:..... Runoff Layer
Initial Julian date (IDATEZ)..... 2007267
Initial time of day in seconds (TZERO)..... 0.0
No. Transferred input locations..... 12
No. Transferred pollutants..... 0
Size of total catchment area (acres)..... 40.30

Element numbers of interface inlet locations: #
#####

MH 1a	MH 1b	MH 1d	MH 1h	MH 2
MH 3d	MH 3e			
MH 1e	MH 1f	MH 3a	MH 3b	MH 4b

Conversion factor to cfs for flow units on interface file. Multiply by:
35.31467

Important Information #####
Interface file start: 2007/09/24 00:00:00
Simulation start: 2007/09/24 00:00:00
Same date/time found in interface file and model

=====

XP Note Field Summary

=====

=====

Conduit Convergence Criteria

=====

Conduit Name	Full Flow	Conduit Slope
P4a-4c	5.0122	0.0050
P3f-4a	3.7112	0.0060
P3e-3f	2.3948	0.0060
P3d-3e	2.4045	0.0060
P3c-3f	5.2390	0.0096
P2-4c	3.5386	0.0130
P1h-2	3.7938	0.0149
P1g-3c	4.3886	0.0200
P1f-1g	2.4041	0.0060
P1e-1f	2.4039	0.0060
P1c-1h	2.6352	0.0212
P1b-1c	2.2951	0.0055

		12851_Storm Model.out
P1a-1b	2.3819	0.0059
P3b-3c	2.4099	0.0060
P3a-3b	2.3940	0.0060
P4c-4d	2.2906	0.0029
P1d-1c	2.6276	0.0072
P4b-4c	2.3688	0.0058
Link25	99.9586	0.5000
orifice_1	0.0338	0.0000

```

=====
| Initial Model Condition |
| Initial Time = 0.01 hours |
=====

```

	Junction /	Depth /	Elevation	====>	"*" Junction is Surcharged.
	MH 1a/	0.00 /	938.51		MH 1e/ 0.00 / 938.51
MH 1f/	0.00 /	937.77			
	MH 1b/	0.00 /	937.78		MH 1d/ 0.00 / 937.22
MH 1c/	0.00 /	936.41			
	MH 1g/	0.00 /	936.51		MH 1h/ 0.00 / 936.06
MH 3a/	0.00 /	935.32			
	MH 3d/	0.00 /	935.29		MH 2/ 0.00 / 934.45
MH 3b/	0.00 /	934.28			
	MH 3e/	0.00 /	934.26		MH 4b/ 0.00 / 933.63
MH 3f/	0.00 /	932.52			
	MH 3c/	0.00 /	932.66		MH 4a/ 0.00 / 932.31
MH 4c/	0.00 /	932.24			
	MH 4d/	0.00 /	930.50		orifice/ 0.00 / 930.50
Node22/	0.00 /	925.50			

	Conduit/	FLOW	====>	"*" Conduit uses the normal flow option.
	P4a-4c/	0.00		P3f-4a/ 0.00 P3e-3f/
0.00				
	P3d-3e/	0.00		P3c-3f/ 0.00 P2-4c/
0.00				
	P1h-2/	0.00		P1g-3c/ 0.00 P1f-1g/
0.00				
	P1e-1f/	0.00		P1c-1h/ 0.00 P1b-1c/
0.00				
	P1a-1b/	0.00		P3b-3c/ 0.00 P3a-3b/
0.00				
	P4c-4d/	0.00		P1d-1c/ 0.00 P4b-4c/
0.00				
	Link25/	0.00		orifice_1/ 0.00 FREE # 1/
0.00				

	Conduit/	velocity		
	P4a-4c/	0.00		P3f-4a/ 0.00 P3e-3f/
0.00				
	P3d-3e/	0.00		P3c-3f/ 0.00 P2-4c/
0.00				
	P1h-2/	0.00		P1g-3c/ 0.00 P1f-1g/
0.00				
	P1e-1f/	0.00		P1c-1h/ 0.00 P1b-1c/
0.00				

12851_Storm Model.out

0.00	P1a-1b/	0.00	P3b-3c/	0.00	P3a-3b/
0.00	P4c-4d/	0.00	P1d-1c/	0.00	P4b-4c/
	Link25/	0.00	orifice_1/	0.00	
	Conduit/ Cross Sectional Area				
0.00	P4a-4c/	0.00	P3f-4a/	0.00	P3e-3f/
0.00	P3d-3e/	0.00	P3c-3f/	0.00	P2-4c/
0.00	P1h-2/	0.00	P1g-3c/	0.00	P1f-1g/
0.00	P1e-1f/	0.00	P1c-1h/	0.00	P1b-1c/
0.00	P1a-1b/	0.00	P3b-3c/	0.00	P3a-3b/
0.00	P4c-4d/	0.00	P1d-1c/	0.00	P4b-4c/
0.00	Link25/	0.00	orifice_1/	0.00	
	Conduit/ Hydraulic Radius				
0.00	P4a-4c/	0.00	P3f-4a/	0.00	P3e-3f/
0.00	P3d-3e/	0.00	P3c-3f/	0.00	P2-4c/
0.00	P1h-2/	0.00	P1g-3c/	0.00	P1f-1g/
0.00	P1e-1f/	0.00	P1c-1h/	0.00	P1b-1c/
0.00	P1a-1b/	0.00	P3b-3c/	0.00	P3a-3b/
0.00	P4c-4d/	0.00	P1d-1c/	0.00	P4b-4c/
0.00	Link25/	0.00	orifice_1/	0.00	
	Conduit/ Upstream/ Downstream Elevation				
P3e-3f/	P4a-4c/	932.24/	932.24	P3f-4a/	932.31/ 932.31
	932.52/	932.52			
P2-4c/	P3d-3e/	934.26/	934.26	P3c-3f/	932.52/ 932.52
	932.24/	932.24			
P1f-1g/	P1h-2/	934.45/	934.45	P1g-3c/	932.66/ 932.66
	936.51/	936.51			
P1b-1c/	P1e-1f/	937.77/	937.77	P1c-1h/	936.06/ 936.06
	936.41/	936.41			
P3a-3b/	P1a-1b/	937.78/	937.78	P3b-3c/	932.66/ 932.66
	934.28/	934.28			
P4b-4c/	P4c-4d/	930.50/	930.50	P1d-1c/	936.41/ 936.41
	932.24/	932.24			
	Link25/	925.50/	925.50	orifice_1/	930.50/ 930.50

====> System inflows (file) at 4.17 hours (Junction / Inflow, cu m/s)

MH 1a	/ 8.57E-03	MH 1b	/ 1.24E-02	MH 1d	/ 5.44E-03	MH 1h	/ 5.64E-03
MH 2	/ 8.87E-03	MH 3d	/ 1.50E-02				
MH 3e	/ 9.78E-03	MH 1e	/ 7.90E-03	MH 1f	/ 1.20E-02	MH 3a	/ 9.53E-03
MH 3b	/ 9.32E-03	MH 4b	/ 4.03E-03				

Cycle 500 Time 4 Hrs - 10.00 Min

Junction / Depth / Elevation			====>	"*" Junction is Surcharged.		
MH 1a/	0.02 /	938.53		MH 1e/	0.02 /	938.53
MH 1f/	0.03 /	937.80				

12851_Storm Model.out

MH 1c/	MH 1b/	0.03 /	937.81	MH 1d/	0.01 /	937.24
	0.07 /	936.48				
	MH 1g/	0.02 /	936.53	MH 1h/	0.05 /	936.11
MH 3a/	0.02 /	935.34				
	MH 3d/	0.03 /	935.32	MH 2/	0.04 /	934.49
MH 3b/	0.03 /	934.31				
	MH 3e/	0.04 /	934.30	MH 4b/	0.01 /	933.64
MH 3f/	0.04 /	932.56				
	MH 3c/	0.11 /	932.76	MH 4a/	0.12 /	932.44
MH 4c/	0.08 /	932.32				
	MH 4d/	0.13 /	930.63	orifice/	0.02 /	930.51
Node22/	0.00 /	925.50				

	Conduit/	FLOW	====>	"*" Conduit uses	the normal	flow option.
0.02	P4a-4c/	0.06		P3f-4a/	0.06*	P3e-3f/
	P3d-3e/	0.01*				
0.03	P3c-3f/	0.04		P2-4c/	0.04	P1h-2/
	P1g-3c/	0.02*				
0.03	P1f-1g/	0.02		P1e-1f/	0.01	P1c-1h/
	P1b-1c/	0.02				
0.01*	P1a-1b/	0.01*		P3b-3c/	0.02	P3a-3b/
	P4c-4d/	0.11				
0.01	P1d-1c/	0.01		P4b-4c/	0.00	Link25/
	Orifice_1/	0.01				
	FREE # 1/	0.01				

====> System inflows (file) at 8.33 hours (Junction / Inflow, cu m/s)

MH 1a	/	3.42E-02	MH 1b	/	4.87E-02	MH 1d	/	1.89E-02	MH 1h	/	1.79E-02
MH 2	/	2.97E-02	MH 3d	/	5.25E-02						
MH 3e	/	3.83E-02	MH 1e	/	2.75E-02	MH 1f	/	4.16E-02	MH 3a	/	3.38E-02
MH 3b	/	3.47E-02	MH 4b	/	1.32E-02						

Cycle 1000 Time 8 Hrs - 20.00 Min

	Junction /	Depth /	Elevation	====>	"*" Junction is	Surcharged.
	MH 1a/	0.04 /	938.56		MH 1e/	0.04 / 938.55
MH 1f/	0.07 /	937.84				
	MH 1b/	0.08 /	937.85		MH 1d/	0.03 / 937.25
MH 1c/	0.13 /	936.55				
	MH 1g/	0.05 /	936.56		MH 1h/	0.09 / 936.15
MH 3a/	0.04 /	935.36				
	MH 3d/	0.06 /	935.35		MH 2/	0.08 / 934.53
MH 3b/	0.07 /	934.34				
	MH 3e/	0.08 /	934.34		MH 4b/	0.03 / 933.65
MH 3f/	0.10 /	932.61				
	MH 3c/	0.18 /	932.84		MH 4a/	0.22 / 932.53
MH 4c/	0.17 /	932.40				
	MH 4d/	0.74 /	931.24		orifice/	0.03 / 930.53
Node22/	0.01 /	925.51				

	Conduit/	FLOW	====>	"*" Conduit uses	the normal	flow option.
0.10	P4a-4c/	0.25		P3f-4a/	0.25	P3e-3f/
	P3d-3e/	0.05*				
0.13	P3c-3f/	0.15		P2-4c/	0.16	P1h-2/
	P1g-3c/	0.07*				
0.11	P1f-1g/	0.07		P1e-1f/	0.03*	P1c-1h/
	P1b-1c/	0.09				
0.03*	P1a-1b/	0.03*		P3b-3c/	0.07	P3a-3b/
	P4c-4d/	0.42				
0.05	P1d-1c/	0.02		P4b-4c/	0.01	Link25/
	Orifice_1/	0.05				
	FREE # 1/	0.05				

12851_Storm Model.out

====> System inflows (file) at 12.50 hours (Junction / Inflow, cu m/s)

MH 1a	/ 1.12E-02	MH 1b	/ 1.62E-02	MH 1d	/ 6.71E-03	MH 1h	/ 6.89E-03
MH 2	/ 1.10E-02	MH 3d	/ 1.89E-02				
MH 3e	/ 1.29E-02	MH 1e	/ 9.86E-03	MH 1f	/ 1.51E-02	MH 3a	/ 1.20E-02
MH 3b	/ 1.20E-02	MH 4b	/ 4.93E-03				

Cycle 1500 Time 12 Hrs - 30.00 Min

	Junction /	Depth /	Elevation	====>	"*" Junction is Surcharged.
	MH 1a/	0.02 /	938.54		MH 1e/ 0.02 / 938.54
MH 1f/	0.04 /	937.81			
	MH 1b/	0.04 /	937.82		MH 1d/ 0.02 / 937.24
MH 1c/	0.08 /	936.49			
	MH 1g/	0.03 /	936.54		MH 1h/ 0.06 / 936.12
MH 3a/	0.02 /	935.34			
	MH 3d/	0.03 /	935.33		MH 2/ 0.04 / 934.49
MH 3b/	0.04 /	934.31			
	MH 3e/	0.04 /	934.30		MH 4b/ 0.02 / 933.64
MH 3f/	0.05 /	932.57			
	MH 3c/	0.12 /	932.78		MH 4a/ 0.14 / 932.45
MH 4c/	0.09 /	932.33			
	MH 4d/	0.99 /	931.49		orifice/ 0.04 / 930.53
Node22/	0.01 /	925.51			

	Conduit/	FLOW	====>	"*" Conduit uses the normal flow option.
	P4a-4c/	0.08		P3f-4a/ 0.08 P3e-3f/
0.03	P3d-3e/	0.02*		
	P3c-3f/	0.05		P2-4c/ 0.05 P1h-2/
0.04	P1g-3c/	0.03*		
	P1f-1g/	0.03		P1e-1f/ 0.01 P1c-1h/
0.03	P1b-1c/	0.03		
	P1a-1b/	0.01*		P3b-3c/ 0.02 P3a-3b/
0.01*	P4c-4d/	0.14		
	P1d-1c/	0.01		P4b-4c/ 0.00 Link25/
0.05	Orifice_1/	0.05		
	FREE # 1/	0.05		

====> System inflows (file) at 16.67 hours (Junction / Inflow, cu m/s)

MH 1a	/ 8.12E-03	MH 1b	/ 1.17E-02	MH 1d	/ 4.90E-03	MH 1h	/ 5.04E-03
MH 2	/ 8.04E-03	MH 3d	/ 1.37E-02				
MH 3e	/ 9.31E-03	MH 1e	/ 7.19E-03	MH 1f	/ 1.10E-02	MH 3a	/ 8.71E-03
MH 3b	/ 8.72E-03	MH 4b	/ 3.61E-03				

Cycle 2000 Time 16 Hrs - 40.00 Min

	Junction /	Depth /	Elevation	====>	"*" Junction is Surcharged.
	MH 1a/	0.02 /	938.53		MH 1e/ 0.02 / 938.53
MH 1f/	0.03 /	937.80			
	MH 1b/	0.03 /	937.81		MH 1d/ 0.01 / 937.24
MH 1c/	0.07 /	936.48			
	MH 1g/	0.02 /	936.53		MH 1h/ 0.05 / 936.11
MH 3a/	0.02 /	935.34			
	MH 3d/	0.03 /	935.32		MH 2/ 0.04 / 934.48
MH 3b/	0.03 /	934.31			
	MH 3e/	0.04 /	934.30		MH 4b/ 0.01 / 933.64
MH 3f/	0.04 /	932.56			
	MH 3c/	0.10 /	932.76		MH 4a/ 0.12 / 932.43
MH 4c/	0.08 /	932.31			
	MH 4d/	1.09 /	931.59		orifice/ 0.04 / 930.53
Node22/	0.02 /	925.52			

12851_Storm Model.out

```

Conduit/      FLOW  ==> "*" Conduit uses the normal flow option.
P4a-4c/      0.06      P3f-4a/      0.06      P3e-3f/
0.02          P3d-3e/      0.01*
P3c-3f/      0.04          P2-4c/      0.04          P1h-2/
0.03          P1g-3c/      0.02*
P1f-1g/      0.02          P1e-1f/      0.01          P1c-1h/
0.02          P1b-1c/      0.02
P1a-1b/      0.01*      P3b-3c/      0.02          P3a-3b/
0.01*          P4c-4d/      0.10
P1d-1c/      0.00          P4b-4c/      0.00          Link25/
0.06          Orifice_1/      0.06
FREE # 1/      0.06

```

==> System inflows (file) at 20.83 hours (Junction / Inflow, cu m/s)

```

MH 1a / 6.63E-03 MH 1b / 9.58E-03 MH 1d / 4.02E-03 MH 1h / 4.13E-03
MH 2 / 6.59E-03 MH 3d / 1.13E-02
MH 3e / 7.61E-03 MH 1e / 5.89E-03 MH 1f / 8.98E-03 MH 3a / 7.14E-03
MH 3b / 7.13E-03 MH 4b / 2.96E-03

```

Cycle 2500 Time 20 Hrs - 50.00 Min

```

Junction / Depth / Elevation ==> "*" Junction is Surcharged.
MH 1a/ 0.02 / 938.53 MH 1e/ 0.02 / 938.53
MH 1f/ 0.03 / 937.80
MH 1b/ 0.03 / 937.81
MH 1c/ 0.06 / 936.47 MH 1d/ 0.01 / 937.24
MH 1g/ 0.02 / 936.53 MH 1h/ 0.05 / 936.11
MH 3a/ 0.02 / 935.34
MH 3d/ 0.02 / 935.32 MH 2/ 0.03 / 934.48
MH 3b/ 0.03 / 934.30
MH 3e/ 0.03 / 934.29
MH 3f/ 0.03 / 932.55
MH 3c/ 0.10 / 932.76
MH 4c/ 0.07 / 932.31
MH 4d/ 1.14 / 931.64
Node22/ 0.02 / 925.52 orifice/ 0.04 / 930.53

```

```

Conduit/      FLOW  ==> "*" Conduit uses the normal flow option.
P4a-4c/      0.05      P3f-4a/      0.05      P3e-3f/
0.02          P3d-3e/      0.01*
P3c-3f/      0.03          P2-4c/      0.03          P1h-2/
0.02          P1g-3c/      0.01*
P1f-1g/      0.01          P1e-1f/      0.01          P1c-1h/
0.02          P1b-1c/      0.02
P1a-1b/      0.01*      P3b-3c/      0.01          P3a-3b/
0.01*          P4c-4d/      0.08
P1d-1c/      0.00          P4b-4c/      0.00          Link25/
0.06          Orifice_1/      0.06
FREE # 1/      0.06

```

```

*=====*
| Table E5 - Junction Time Limitation Summary |
| (0.10 or 0.25)* Depth * Area |
| Time step = ----- |
| Sum of Flow |
|=====*
| The time this junction was the limiting junction |
| is listed in the third column. |
|=====*

```

Junction	Time(.10)	12851_Storm Time(.25)	Model.out Time(sec)
MH 1a	136.6583	300.0000	86400.0000
MH 1e	86.1453	215.3633	0.0000
MH 1f	120.8225	300.0000	0.0000
MH 1b	156.0578	300.0000	0.0000
MH 1d	102.8907	257.2268	0.0000
MH 1c	81.4178	203.5446	0.0000
MH 1g	138.9497	300.0000	0.0000
MH 1h	69.0029	172.5073	0.0000
MH 3a	98.1646	245.4115	0.0000
MH 3d	69.3183	173.2957	0.0000
MH 2	87.3497	218.3741	0.0000
MH 3b	157.4511	300.0000	0.0000
MH 3e	135.3980	300.0000	0.0000
MH 4b	101.2339	253.0848	0.0000
MH 3f	59.1920	147.9801	0.0000
MH 3c	205.2361	300.0000	0.0000
MH 4a	239.5276	300.0000	0.0000
MH 4c	57.7826	144.4564	0.0000
MH 4d	122.8629	300.0000	0.0000
orifice	300.0000	300.0000	0.0000
Node22	300.0000	300.0000	0.0000

The junction requiring the smallest time step was...MH 1a

=====	
Table E5a - Conduit Explicit Condition Summary	
Courant	= Conduit Length
Time step	= -----
	velocity + sqrt(g*depth)
Conduit Implicit Condition Summary	
Courant	= Conduit Length
Time step	= -----
	velocity
=====	
The 3rd column is the Explicit time step times the minimum courant time step factor	
Minimum Conduit Time Step in seconds in the 4th column in the list. Maximum possible is 10 * maximum time step	

12851_Storm Model.out

The 5th column is the maximum change at any time step during the simulation. The 6th column is the wobble value which is an indicator of the flow stability.

You should use this section to find those conduits that are slowing your model down. Use modify conduits to alter the length of the slow conduits to make your simulation faster, or change the conduit name to "CHME?????" where ????? are any characters, this will lengthen the conduit based on the model time step, not the value listed in modify conduits.

Type of Soln	Conduit	Time(exp)	Expl*Cmin	Time(imp)	Time(min)	Max Qchange	Wobble
Normal Soln	P4a-4c	3.3992	3.3992	5.9945	66.0000	0.0090	0.4299
Normal Soln	P3f-4a	12.8589	12.8589	26.9941	0.0000	0.0088	0.5793
Normal Soln	P3e-3f	46.5663	46.5663	81.7188	0.0000	0.0036	0.3552
Normal Soln	P3d-3e	72.5542	72.5542	129.4840	0.0000	0.0027	0.2730
Normal Soln	P3c-3f	3.6853	3.6853	6.1363	0.0000	0.0056	0.2544
Normal Soln	P2-4c	46.2228	46.2228	69.7125	0.0000	0.0056	0.3910
Normal Soln	P1h-2	28.2110	28.2110	41.9021	0.0000	0.0043	0.2725
Normal Soln	P1g-3c	72.8184	72.8184	119.8762	0.0000	0.0028	0.1685
Normal Soln	P1f-1g	67.7630	67.7630	119.2115	0.0000	0.0033	0.3126
Normal Soln	P1e-1f	59.9510	59.9510	110.3844	0.0000	0.0015	0.1509
Normal Soln	P1c-1h	3.7215	3.7215	5.7405	37.0000	0.0031	0.2991
Normal Soln	P1b-1c	78.8208	78.8208	142.4345	0.0000	0.0022	0.2528
Normal Soln	P1a-1b	68.0564	68.0564	129.2609	0.0000	-0.0006	0.1103
Normal Soln	P3b-3c	48.8774	48.8774	86.3334	0.0000	0.0027	0.2660
Normal Soln	P3a-3b	84.5281	84.5281	155.0304	0.0000	0.0016	0.1658
Normal Soln	P4c-4d	22.8419	22.8419	44.6601	0.0000	0.0144	1.5627
Normal Soln	P1d-1c	37.9039	37.9039	66.2418	0.0000	0.0012	0.1055
Normal Soln	P4b-4c	34.4619	34.4619	63.1620	0.0000	0.0010	0.0942
Normal Soln	Link25	1.3707	1.3707	1.3756	1337.0000	0.0002	0.0006
Normal Soln	Orifice_1	54.5453	54.5453	140.7233	0.0000	0.0000	1.7885

The conduit with the smallest time step limitation was..Link25
The conduit with the largest wobble was.....Orifice_1
The conduit with the largest flow change in any consecutive time step.....P4c-4d

12851_Storm Model.out

=====

* Hydraulic design routine final results. *

=====

Conduit Name	<----- Original ----->	<----- Designed ----->
P1c-1h	Height Width Barrels	Height Width Barrels
	0.9000 0.9000 1.0000	0.9000 0.9000 1.0000

=====

Table E6. Final Model Condition

This table is used for steady state flow comparison and is the information saved to the hot-restart file.

Final Time = 24.008 hours

=====

Junction / Depth / Elevation	====> "*" Junction is Surcharged.
MH 1a/ 0.02 / 938.53/	MH 1e/ 0.02 / 938.53/
MH 1f/ 0.03 / 937.80/	MH 1d/ 0.01 / 937.24/
MH 1b/ 0.03 / 937.81/	MH 1h/ 0.05 / 936.11/
MH 1c/ 0.06 / 936.47/	MH 2/ 0.03 / 934.48/
MH 1g/ 0.02 / 936.53/	MH 4b/ 0.01 / 933.64/
MH 3a/ 0.02 / 935.34/	MH 4a/ 0.11 / 932.42/
MH 3d/ 0.02 / 935.32/	orifice/ 0.04 / 930.53/
MH 3b/ 0.03 / 934.30/	
MH 3e/ 0.03 / 934.29/	
MH 3f/ 0.03 / 932.55/	
MH 3c/ 0.09 / 932.75/	
MH 4c/ 0.07 / 932.30/	
MH 4d/ 1.16 / 931.66/	
Node22/ 0.02 / 925.52/	

Conduit/ Flow	====> "*" Conduit uses the normal flow option.
P4a-4c/ 0.04 /	P3f-4a/ 0.04 / P3e-3f/
0.02 / P3d-3e/ 0.01*/	P3c-3f/ 0.03 / P2-4c/
0.03 / P1h-2/ 0.02 /	P1g-3c/ 0.01*/ P1f-1g/
0.01 / P1e-1f/ 0.01 /	P1c-1h/ 0.02 / P1b-1c/
0.01 / P1a-1b/ 0.01*/	P3b-3c/ 0.01 / P3a-3b/
0.01*/ P4c-4d/ 0.07 /	P1d-1c/ 0.00 / P4b-4c/
0.00 / Link25/ 0.06 /	orifice_1/ 0.06 / FREE # 1/
0.06 /	

Conduit/ Velocity	
P4a-4c/ 0.87 /	P3f-4a/ 0.50 / P3e-3f/
0.52 / P3d-3e/ 0.42 /	P3c-3f/ 0.87 / P2-4c/
0.80 / P1h-2/ 0.76 /	P1g-3c/ 0.45 / P1f-1g/
0.47 / P1e-1f/ 0.33 /	P1c-1h/ 1.11 / P1b-1c/
0.47 / P1a-1b/ 0.33 /	P3b-3c/ 0.47 / P3a-3b/
0.35 / P4c-4d/ 0.56 /	P1d-1c/ 0.29 / P4b-4c/
0.24 / Link25/ 3.47 /	orifice_1/ 2.13 /

12851_Storm Model.out

1.23 /	Conduit/ P4a-4c/	width 0.73 /	P3f-4a/	2.56 /	P3e-3f/
1.25 /	P3d-3e/	1.18 /	P3c-3f/	0.60 /	P2-4c/
1.20 /	P1h-2/	1.21 /	P1g-3c/	1.20 /	P1f-1g/
1.22 /	P1e-1f/	1.12 /	P1c-1h/	0.42 /	P1b-1c/
1.14 /	P1a-1b/	1.14 /	P3b-3c/	1.20 /	P3a-3b/
1.09 /	P4c-4d/	2.36 /	P1d-1c/	1.10 /	P4b-4c/
	Link25/	0.78 /	orifice_1/	0.02 /	
0.03 /	Junction/ MH 1a/	EGL 0.02 /	MH 1e/	0.02 /	MH 1f/
0.41 /	MH 1b/	0.03 /	MH 1d/	0.01 /	MH 1c/
0.02 /	MH 1g/	0.29 /	MH 1h/	0.11 /	MH 3a/
0.03 /	MH 3d/	0.02 /	MH 2/	0.35 /	MH 3b/
1.07 /	MH 3e/	0.04 /	MH 4b/	0.01 /	MH 3f/
1.04 /	MH 3c/	0.95 /	MH 4a/	0.12 /	MH 4c/
0.63 /	MH 4d/	1.59 /	orifice/	0.27 /	Node22/
0.39 /	Junction/ MH 1a/	Freeboard 0.38 /	MH 1e/	0.38 /	MH 1f/
1.00 /	MH 1b/	0.37 /	MH 1d/	0.39 /	MH 1c/
0.38 /	MH 1g/	0.63 /	MH 1h/	1.14 /	MH 3a/
0.37 /	MH 3d/	0.38 /	MH 2/	0.66 /	MH 3b/
1.40 /	MH 3e/	0.37 /	MH 4b/	0.39 /	MH 3f/
1.65 /	MH 3c/	1.51 /	MH 4a/	1.53 /	MH 4c/
6.48 /	MH 4d/	0.94 /	orifice/	2.07 /	Node22/
0.20 /	Junction/ MH 1a/	Max Volume 0.11 /	MH 1e/	0.14 /	MH 1f/
0.31 /	MH 1b/	0.18 /	MH 1d/	0.11 /	MH 1c/
0.14 /	MH 1g/	0.14 /	MH 1h/	0.21 /	MH 3a/
0.18 /	MH 3d/	0.19 /	MH 2/	0.22 /	MH 3b/
0.30 /	MH 3e/	0.21 /	MH 4b/	0.11 /	MH 3f/
0.44 /	MH 3c/	0.42 /	MH 4a/	0.53 /	MH 4c/
0.02 /	MH 4d/	8598.90 /	orifice/	0.04 /	Node22/

12851_Storm Model.out

	Junction/Total Fldng				
0.00 /	MH 1a/	0.00 /	MH 1e/	0.00 /	MH 1f/
0.00 /	MH 1b/	0.00 /	MH 1d/	0.00 /	MH 1c/
0.00 /	MH 1g/	0.00 /	MH 1h/	0.00 /	MH 3a/
0.00 /	MH 3d/	0.00 /	MH 2/	0.00 /	MH 3b/
0.00 /	MH 3e/	0.00 /	MH 4b/	0.00 /	MH 3f/
0.00 /	MH 3c/	0.00 /	MH 4a/	0.00 /	MH 4c/
0.00 /	MH 4d/	0.00 /	orifice/	0.00 /	Node22/

	Conduit/ Cross Sectional Area				
0.03 /	P4a-4c/	0.05 /	P3f-4a/	0.09 /	P3e-3f/
0.03 /	P3d-3e/	0.02 /	P3c-3f/	0.03 /	P2-4c/
0.03 /	P1h-2/	0.03 /	P1g-3c/	0.03 /	P1f-1g/
0.03 /	P1e-1f/	0.02 /	P1c-1h/	0.02 /	P1b-1c/
0.03 /	P1a-1b/	0.02 /	P3b-3c/	0.03 /	P3a-3b/
0.02 /	P4c-4d/	0.13 /	P1d-1c/	0.01 /	P4b-4c/
0.01 /	Link25/	0.02 /	orifice_1/	0.03 /	

	Conduit/ Final Volume				
3.89 /	P4a-4c/	0.80 /	P3f-4a/	3.06 /	P3e-3f/
5.36 /	P3d-3e/	4.15 /	P3c-3f/	0.49 /	P2-4c/
4.74 /	P1h-2/	2.59 /	P1g-3c/	5.71 /	P1f-1g/
5.55 /	P1e-1f/	1.95 /	P1c-1h/	0.27 /	P1b-1c/
3.23 /	P1a-1b/	2.26 /	P3b-3c/	3.20 /	P3a-3b/
0.70 /	P4c-4d/	9.78 /	P1d-1c/	0.93 /	P4b-4c/
	Link25/	0.17 /	orifice_1/	8.20 /	

	Conduit/ Hydraulic Radius				
0.03 /	P4a-4c/	0.06 /	P3f-4a/	0.03 /	P3e-3f/
0.03 /	P3d-3e/	0.02 /	P3c-3f/	0.05 /	P2-4c/
0.02 /	P1h-2/	0.02 /	P1g-3c/	0.02 /	P1f-1g/
0.02 /	P1e-1f/	0.01 /	P1c-1h/	0.04 /	P1b-1c/
0.02 /	P1a-1b/	0.02 /	P3b-3c/	0.02 /	P3a-3b/
0.01 /	P4c-4d/	0.05 /	P1d-1c/	0.01 /	P4b-4c/
	Link25/	0.02 /	orifice_1/	0.05 /	

Conduit/ Upstream/ Downstream Elevation

			12851_Storm Model.out			
P3e-3f/	P4a-4c/	932.42/	932.30	P3f-4a/	932.55/	932.42
	934.29/	933.58/				
	P3d-3e/	935.32/	934.29	P3c-3f/	932.75/	932.55
P2-4c/	934.48/	932.47/				
	P1h-2/	936.11/	934.76	P1g-3c/	936.53/	932.75
P1f-1g/	937.80/	936.79/				
	P1e-1f/	938.53/	937.80	P1c-1h/	936.47/	936.11
P1b-1c/	937.81/	936.81/				
	P1a-1b/	938.53/	937.81	P3b-3c/	934.30/	933.60
P3a-3b/	935.34/	934.30/				
	P4c-4d/	932.30/	932.07	P1d-1c/	937.24/	936.70
P4b-4c/	933.64/	933.27/				
	Link25/	930.53/	925.52	orifice_1/	931.66/	930.53

=====

| Table E7 - Iteration Summary |

=====

Total number of time steps simulated.....	2880
Total number of passes in the simulation.....	30490
Total number of time steps during simulation....	30484
Ratio of actual # of time steps / NTCYC.....	10.585
Average number of iterations per time step.....	1.000
Average time step size(seconds).....	2.834
Smallest time step size(seconds).....	1.364
Largest time step size(seconds).....	30.000
Average minimum Conduit Courant time step (sec).	4.372
Average minimum implicit time step (sec).....	2.891
Average minimum junction time step (sec).....	2.891
Average Courant Factor Tf.....	2.891
Number of times omega reduced.....	272

=====

| Table E8 - Junction Time Step Limitation Summary |

=====

Not Convr = Number of times this junction did not
converge during the simulation.
Avg Convr = Average junction iterations.
Conv err = Mean convergence error.
Omega Cng = Change of omega during iterations
Max Itern = Maximum number of iterations

	Junction	Not Convr	Avg Convr	Total Itt	Omega Cng	Max Itern	Ittrn >10
Ittrn >25	Ittrn >40						
0	MH 1a	0	1.01	30863	0	4	0
0	MH 1e	0	1.02	31013	0	4	0
0	MH 1f	0	1.04	31824	6	7	0
0	MH 1b	0	1.04	31651	0	6	0
0	MH 1d	0	1.01	30877	0	6	0
0	MH 1c	0	1.09	33088	133	8	0
0	MH 1g	0	1.06	32202	0	7	0
	MH 1h	0	1.08	32802	0	6	0

12851_Storm Model.out							
0	0						
	MH 3a	0	1.02	31095	0	4	0
0	0						
	MH 3d	0	1.03	31282	0	5	0
0	0						
	MH 2	0	1.10	33511	10	13	2
0	0						
	MH 3b	0	1.04	31705	0	6	0
0	0						
	MH 3e	0	1.05	31992	3	7	0
0	0						
	MH 4b	0	1.01	30824	0	6	0
0	0						
	MH 3f	0	1.12	34152	0	7	0
0	0						
	MH 3c	0	1.09	33128	0	7	0
0	0						
	MH 4a	0	1.10	33405	0	5	0
0	0						
	MH 4c	0	1.18	35916	83	8	0
0	0						
	MH 4d	0	1.11	33916	37	8	0
0	0						
	Orifice	0	1.00	30491	0	3	0
0	0						
	Node22	0	1.00	30502	0	6	0
0	0						
Total number of iterations for all junctions..				676239			

Minimum number of possible iterations..... 640164

Efficiency of the simulation..... 1.06

Good Efficiency

=====

| Extran Efficiency is an indicator of the efficiency of |
 | the simulation. Ideal efficiency is one iteration per |
 | time step. Altering the underrelaxation parameter, |
 | lowering the time step, increasing the flow and head |
 | tolerance are good ways of improving the efficiency, |
 | another is lowering the internal time step. The lower the |

12851_Storm Model.out

efficiency generally the faster your model will run.
If your efficiency is less than 1.5 then you may try
increasing your time step so that your overall simulation
is faster. Ideal efficiency would be around 2.0

Good Efficiency < 1.5 mean iterations
Excellent Efficiency < 2.5 and > 1.5 mean iterations
Good Efficiency < 4.0 and > 2.5 mean iterations
Fair Efficiency < 7.5 and > 4.0 mean iterations
Poor Efficiency > 7.5 mean iterations

Table E9 - JUNCTION SUMMARY STATISTICS
The Maximum area is only the area of the node, it
does not include the area of the surrounding conduits

Maximum Junction Area m^2	Maximum Gutter Junction Depth Name meters	Maximum Ground Gutter Elevation width meters	Uppermost Maximum PipeCrown Gutter Elevation Velocity meters m/s	Maximum Junction Elevation meters	Time of Occurrence Hr. Min.	Meters of Surcharge at Max Elevation	Freeboard of node meters
1.2200	MH 1a 0.0000	938.9150 0.0000	938.9150 0.0000	938.6092	7 21	0.0000	0.3058
1.2200	MH 1e 0.0000	938.9140 0.0000	938.9140 0.0000	938.6251	7 21	0.0000	0.2889
1.2200	MH 1f 0.0000	938.1880 0.0000	938.1880 0.0000	937.9362	7 22	0.0000	0.2518
1.2200	MH 1b 0.0000	938.1780 0.0000	938.1780 0.0000	937.9254	7 24	0.0000	0.2526
1.2200	MH 1d 0.0000	937.6230 0.0000	937.6230 0.0000	937.3152	7 21	0.0000	0.3078
1.2200	MH 1c 0.0000	937.4700 0.0000	937.3140 0.0000	936.6654	7 22	0.0000	0.8046
1.2200	MH 1g 0.0000	937.1620 0.0000	937.1620 0.0000	936.6284	7 23	0.0000	0.5336
1.2200	MH 1h 0.0000	937.2500 0.0000	936.9620 0.0000	936.2338	7 21	0.0000	1.0162
1.2200	MH 3a 0.0000	935.7190 0.0000	935.7190 0.0000	935.4360	7 21	0.0000	0.2830
1.2200	MH 3d 0.0000	935.6950 0.0000	935.6950 0.0000	935.4475	7 21	0.0000	0.2475
1.2200	MH 2 0.0000	935.1400 0.0000	935.1400 0.0000	934.6311	7 22	0.0000	0.5089
1.2200	MH 3b 0.0000	934.6770 0.0000	934.6770 0.0000	934.4281	7 23	0.0000	0.2489
1.2200	MH 3e 0.0000	934.6610 0.0000	934.6610 0.0000	934.4363	7 22	0.0000	0.2247
1.2200	MH 4b 0.0000	934.0260 0.0000	934.0260 0.0000	933.7126	7 21	0.0000	0.3134
1.2200	MH 3f 0.0000	933.9510 0.0000	933.9510 0.0000	932.7683	7 24	0.0000	1.1827
1.2200	MH 3c 0.0000	934.2600 0.0000	934.0270 0.0000	932.9997	7 24	0.0000	1.2603
1.2200	MH 4a 0.0000	933.9500 0.0000	933.8170 0.0000	932.7475	7 24	0.0000	1.2025

12851_Storm Model.out

1.2200	MH 4c	933.9500	933.7360	932.5975	7	24	0.0000	1.3525
	0.0000	0.0000	0.0000					
	MH 4d	932.6000	932.4220	931.6570	24	0	0.0000	0.9430
8924.9553	0.0000	0.0000	0.0000					
	orifice	932.6000	932.5000	930.5337	24	0	0.0000	2.0663
1.2200	0.0000	0.0000	0.0000					
	Node22	932.0000	927.5000	925.5157	24	0	0.0000	6.4843
1.2200	0.0000	0.0000	0.0000					

=====

Table E10 - CONDUIT SUMMARY STATISTICS

Note: The peak flow may be less than the design flow and the conduit may still surcharge because of the downstream boundary conditions.

* denotes an open conduit that has been overtopped this is a potential source of severe errors

=====

Ratio of	Maximum Water	Conduit	Maximum	Maximum	Time	Maximum	Time
Max. to	Elev at Pipe	Ratio	Vertical	Computed	of	Computed	of
Design	Upstream	Design	Depth	Flow	Occurrence	Velocity	Occurrence
Flow	Name	Flow	US DS	(cms)	Hr. Min.	(m/s)	Hr. Min.
	(m)	(cms)	(m/s)	(mm)			
0.2192	P4a-4c	5.0122	2.8363	1500.000	1.0988	7	24
	932.7475	932.5975	0.287	0.241			
0.2952	P3f-4a	3.7112	2.6135	435.5191	1.0956	7	24
	932.7683	932.7475	0.561	1.000 *			
0.1811	P3e-3f	2.3948	2.3027	400.0000	0.4336	7	23
	934.4363	933.7260	0.438	0.437			
0.1384	P3d-3e	2.4045	2.3120	400.0000	0.3327	7	21
	935.4475	934.4363	0.381	0.438			
0.1297	P3c-3f	5.2390	3.6601	1350.000	0.6793	7	24
	932.9997	932.7683	0.239	0.185			
0.1993	P2-4c	3.5386	3.4025	400.0000	0.7053	7	22
	934.6311	932.6246	0.460	0.459			
0.1385	P1h-2	3.7938	3.6479	400.0000	0.5254	7	22
	936.2338	934.8922	0.382	0.381			
0.0857	P1g-3c	4.3886	4.2198	400.0000	0.3763	7	23
	936.6284	932.9997	0.296	0.852			
0.1590	P1f-1g	2.4041	2.3116	400.0000	0.3823	7	22
	937.9362	936.9256	0.410	0.409			
0.0761	P1e-1f	2.4039	2.3114	400.0000	0.1830	7	21
	938.6251	937.9362	0.278	0.370			
0.1528	P1c-1h	2.6352	4.1423	900.0000	0.4028	7	22
	936.6654	936.2338	0.279	0.191			
0.1295	P1b-1c	2.2951	2.2068	400.0000	0.2972	7	24
	937.9254	936.9351	0.368	0.368			
0.0562	P1a-1b	2.3819	2.2903	400.0000	0.1338	7	21
	938.6092	937.9254	0.236	0.368			
0.1356	P3b-3c	2.4099	2.3173	400.0000	0.3269	7	23
	934.4281	933.7236	0.378	0.376			
0.0838	P3a-3b	2.3940	2.3019	400.0000	0.2007	7	21
	935.4360	934.4281	0.293	0.378			
0.7973	P4c-4d	2.2906	1.7896	400.0000	1.8263	7	24
	932.5975	932.3771	0.891	0.888			
0.0534	P1d-1c	2.6276	2.5265	400.0000	0.1402	7	21
	937.3152	936.7814	0.231	0.228			

12851_Storm Model.out

P4b-4c	2.3688	2.2777	400.0000	0.1127	7	21	0.9835	7	21
0.0476 933.7126	933.3518	0.217	0.214						
Link25	99.9586	31.8178	2000.000	0.0582	24	0	7.2694	1	42
0.0006 930.5337	925.5157	0.017	.0078						
orifice_1	0.0338	0.1467	192.1561	0.0582	24	0	2.1319	24	0
1.7244 931.6570	930.5337	6.021	0.191						
FREE # 1	Undefnd	Undefnd	Undefn	0.0582	24	0			

=====

Table E11. Area assumptions used in the analysis
Subcritical and Critical flow assumptions from
Subroutine Head. See manual for more information.

=====

Maximum Vel*D (m ² /s)	Conduit Name	Duration of Dry Flow(min)	Duration of Sub- Critical Flow(min)	Durat. of Upstream Critical Flow(min)	Durat. of Downstream Critical Flow(min)	Maximum Hydraulic Radius-m	Maximum X-Sect Area(m ²)
1.0588	P4a-4c	69.6667	1370.3333	0.0000	0.0000	0.2436	0.4103
0.4449	P3f-4a	59.0000	1381.0000	0.0000	0.0000	0.2052	0.8370
0.2548	P3e-3f	46.0000	0.0000	0.0000	1394.0000	0.1218	0.2981
0.2132	P3d-3e	45.0000	1395.0000	0.0000	0.0000	0.1094	0.2486
0.7620	P3c-3f	73.8333	1366.1667	0.0000	0.0000	0.1865	0.2545
0.4063	P2-4c	45.0000	0.0000	0.0000	1395.0000	0.1268	0.3196
0.3259	P1h-2	51.0000	0.0000	0.0000	1389.0000	0.1088	0.2459
0.3622	P1g-3c	46.0000	1394.0000	0.0000	0.0000	0.1003	0.2363
0.2308	P1f-1g	46.0000	0.0000	0.0000	1394.0000	0.1154	0.2718
0.1385	P1e-1f	45.0000	463.1111	0.0000	931.8889	0.0856	0.1669
0.6105	P1c-1h	50.0000	1390.0000	0.0000	0.0000	0.1408	0.1392
0.1869	P1b-1c	46.0000	0.0000	0.0000	1394.0000	0.1056	0.2342
0.1136	P1a-1b	45.0000	1395.0000	0.0000	0.0000	0.0759	0.1391
0.2037	P3b-3c	46.0000	0.0000	0.0000	1394.0000	0.1078	0.2422
0.1480	P3a-3b	45.0000	1395.0000	0.0000	0.0000	0.0890	0.1774
0.5951	P4c-4d	45.0000	0.0000	0.0000	1395.0000	0.2571	1.0934
0.1021	P1d-1c	45.0000	0.0000	0.0000	1395.0000	0.0716	0.1260
0.0831	P4b-4c	45.0000	0.0000	0.0000	1395.0000	0.0679	0.1165
0.0856	Link25	102.3750	1337.6250	0.0000	0.0000	0.0239	0.0168
	orifice_1	61.0000	1379.0000	0.0000	0.0000	0.0538	0.0276

1.2724

=====

| Table E12. Mean Conduit Flow Information |

=====

Mean Cross Area	Mean Conduit Roughness Name	Mean Flow (cms)	Total Flow (m ³)	Mean Percent Change	Low Flow Weightng	Mean Froude Number	Mean Hydraulic Radius
-----	-----	-----	-----	-----	-----	-----	-----
0.0767	P4a-4c 0.0130	0.0894	7720.3393	0.0000	0.9942	1.1332	0.0815
0.1386	P3f-4a 0.0130	0.0894	7726.0601	0.0000	0.9957	0.9392	0.0485
0.0510	P3e-3f 0.0130	0.0351	3030.8882	0.0000	0.9969	1.0081	0.0362
0.0376	P3d-3e 0.0130	0.0212	1828.1732	0.0000	0.9969	0.9466	0.0285
0.0467	P3c-3f 0.0130	0.0544	4696.1797	0.0000	0.9934	1.5729	0.0602
0.0549	P2-4c 0.0130	0.0579	5000.5206	0.0000	0.9969	1.5015	0.0383
0.0448	P1h-2 0.0130	0.0455	3932.0568	0.0000	0.9966	1.5771	0.0328
0.0440	P1g-3c 0.0130	0.0279	2410.1509	0.0000	0.9969	1.1572	0.0297
0.0436	P1f-1g 0.0130	0.0279	2411.1793	0.0000	0.9969	0.9997	0.0321
0.0243	P1e-1f 0.0130	0.0111	960.2296	0.0000	0.9969	0.9403	0.0200
0.0266	P1c-1h 0.0130	0.0377	3254.4150	0.0000	0.9968	1.7711	0.0475
0.0476	P1b-1c 0.0130	0.0300	2591.3238	0.0000	0.9969	0.9607	0.0343
0.0280	P1a-1b 0.0130	0.0123	1063.3792	0.0000	0.9969	0.8713	0.0223

12851_Storm Model.out

0.0424	P3b-3c 0.0130	0.0266	2298.3885	0.0000	0.9969	0.9983	0.0314
0.0285	P3a-3b 0.0130	0.0134	1160.9923	0.0000	0.9969	0.9014	0.0228
0.2002	P4c-4d 0.0130	0.1528	13198.645	0.0000	0.9969	0.8250	0.0758
0.0182	P1d-1c 0.0130	0.0077	663.2812	0.0000	0.9969	1.0106	0.0156
0.0164	P4b-4c 0.0130	0.0056	486.6271	0.0000	0.9969	0.9243	0.0142
0.0143	Link25 0.0140	0.0412	3556.4134	0.0000	0.9872	9.5364	0.0210
0.0257	Orifice_1 0.0029	0.0412	3557.2720	0.0000	0.9949	3.0694	0.0447
	FREE # 1	0.0412	3556.3142				

=====

Table E13. Channel losses(H), headwater depth (HW), tailwater depth (TW), critical and normal depth (Yc and Yn). Use this section for culvert comparisons
--

=====

TW	Conduit	Maximum	Head	Friction	Critical	Normal	HW
Elevat	Name	Flow	Loss	Loss	Depth	Depth	Elevat
932.5946	P4a-4c Max Flow	1.0980	0.0000	0.1297	0.5313	0.4769	932.7464
932.7464	P3f-4a Max Flow	1.0916	0.0000	0.0856	0.2503	0.2045	932.7670
933.7258	P3e-3f Max Flow	0.4330	0.0000	0.7045	0.2033	0.1748	934.4363
934.4235	P3d-3e Max Flow	0.3250	0.0000	0.9782	0.1740	0.1503	935.4466
932.7670	P3c-3f Max Flow	0.6792	0.0000	0.1858	0.4275	0.3280	932.9995
932.6239	P2-4c Max Flow	0.7000	0.0000	1.9763	0.2620	0.1829	934.6309
934.8922	P1h-2 Max Flow	0.5252	0.0000	1.3370	0.2254	0.1522	936.2336
932.9977	P1g-3c Max Flow	0.3735	0.0000	1.7533	0.1877	0.1177	936.6280

12851_Storm Model.out							
936.9255	P1f-1g	0.3818	0.0000	1.0133	0.1900	0.1635	937.9355
	Max Flow						
937.9284	P1e-1f	0.1814	0.0000	0.6556	0.1255	0.1105	938.6246
	Max Flow						
936.2312	P1c-1h	0.4018	0.0000	0.3211	0.3672	0.2370	936.6652
	Max Flow						
936.9349	P1b-1c	0.2965	0.0000	0.9833	0.1654	0.1469	937.9253
	Max Flow						
937.9199	P1a-1b	0.1337	0.0000	0.6092	0.1051	0.0941	938.6092
	Max Flow						
933.7233	P3b-3c	0.3258	0.0000	0.6966	0.1743	0.1503	934.4280
	Max Flow						
934.4170	P3a-3b	0.1971	0.0000	0.9627	0.1316	0.1157	935.4349
	Max Flow						
932.3763	P4c-4d	1.8185	0.0000	0.2208	0.3629	0.3543	932.5946
	Max Flow						
936.7804	P1d-1c	0.1375	0.0000	0.5126	0.1069	0.0904	937.3148
	Max Flow						
933.3511	P4b-4c	0.1112	0.0000	0.3476	0.0945	0.0851	933.7124
	Max Flow						
925.5157	Link25	0.0582	0.0000	3.4296	0.1045	0.0157	930.5337
	Max Flow						
930.5337	Orifice_1	0.0582	0.0000	0.6929	0.2003	0.1922	931.6570
	Max Flow						

=====

Table E13a. CULVERT ANALYSIS CLASSIFICATION, and the time the culvert was in a particular classification during the simulation. The time is in minutes. The Dynamic Wave Equation is used for all conduit analysis but the culvert flow classification condition is based on the HW and TW depths.

=====

		Mild Slope Critical D	Mild Slope TW Control	Steep Slope TW Insignf	Slug Flow Outlet/	Mild Slope TW > D	Mild Slope TW <= D
Outlet Control	Conduit Inlet Name Control	Outlet Inlet Control Configuration	Outlet Control	Entrance Control	Entrance Control	Outlet Control	Outlet Control

662.0000	P4a-4c	0.0000	0.0000	778.0000	0.0000	0.0000	0.0000
	0.0000 None						
80.0000	P3f-4a	0.0000	30.0000	1330.0000	0.0000	0.0000	0.0000
	0.0000 None						
0.0000	P3e-3f	26.0000	15.0000	1399.0000	0.0000	0.0000	0.0000
	0.0000 None						
0.0000	P3d-3e	25.0000	43.0000	1372.0000	0.0000	0.0000	0.0000
	0.0000 None						
20.0000	P3c-3f	0.0000	0.0000	1420.0000	0.0000	0.0000	0.0000
	0.0000 None						
0.0000	P2-4c	0.0000	0.0000	1440.0000	0.0000	0.0000	0.0000
	0.0000 None						
0.0000	P1h-2	0.0000	0.0000	1440.0000	0.0000	0.0000	0.0000
	0.0000 None						
0.0000	P1g-3c	0.0000	0.0000	1440.0000	0.0000	0.0000	0.0000
	0.0000 None						
0.0000	P1f-1g	28.0000	13.0000	1399.0000	0.0000	0.0000	0.0000
	0.0000 None						
0.0000	P1e-1f	251.0000	734.0000	455.0000	0.0000	0.0000	0.0000

12851_Storm Model.out

0.0000	0.0000	None					
	P1c-1h	0.0000	0.0000	1440.0000	0.0000	0.0000	0.0000
0.0000	0.0000	None					
	P1b-1c	147.0000	394.0000	899.0000	0.0000	0.0000	0.0000
0.0000	0.0000	None					
	P1a-1b	1.0000	969.0000	470.0000	0.0000	0.0000	0.0000
0.0000	0.0000	None					
	P3b-3c	22.0000	28.0000	1390.0000	0.0000	0.0000	0.0000
0.0000	0.0000	None					
	P3a-3b	2.0000	846.0000	592.0000	0.0000	0.0000	0.0000
0.0000	0.0000	None					
	P4c-4d	378.0000	1000.0000	45.0000	0.0000	0.0000	0.0000
17.0000	0.0000	None					
	P1d-1c	0.0000	0.0000	1440.0000	0.0000	0.0000	0.0000
0.0000	0.0000	None					
	P4b-4c	329.0000	971.0000	140.0000	0.0000	0.0000	0.0000
0.0000	0.0000	None					
	Link25	0.0000	0.0000	1440.0000	0.0000	0.0000	0.0000
0.0000	0.0000	None					
	orifice_1	347.0000	0.0000	65.0000	0.0000	0.0000	0.0000
1028.0000	0.0000	None					

 | Kinematic Wave Approximations |
 | Time in Minutes for Each Condition |

Conduit Name	Duration of Normal Flow	Slope Criteria	Super- Critical	Roll Waves
P4a-4c	7.3333	9.3333	1350.0000	0.0000
P3f-4a	339.6833	1365.3333	10.5000	0.0000
P3e-3f	0.7841	0.8295	1082.0000	0.0000
P3d-3e	1341.4000	1369.0000	101.1833	0.0000
P3c-3f	3.3333	4.6667	1364.3333	0.0000
P2-4c	1.5136	7.5136	1395.0000	0.0000
P1h-2	1.2000	3.2000	1388.5000	0.0000
P1g-3c	1372.0000	1394.0000	1394.0000	0.0000
P1f-1g	0.3682	0.3682	1010.7500	0.0000
P1e-1f	294.7500	347.5000	62.1000	0.0000
P1c-1h	31.6667	41.5000	1384.5000	0.0000
P1b-1c	0.3182	0.3182	1054.8000	0.0000
P1a-1b	1336.3000	1395.0000	61.0500	0.0000
P3b-3c	0.6909	0.6909	1037.0500	0.0000
P3a-3b	1341.9500	1369.5000	37.0591	0.0000
P4c-4d	1.6182	11.1182	18.0000	0.0000
P1d-1c	0.1455	5.1455	1145.5000	0.0000
P4b-4c	0.0955	9.5955	39.9045	0.0000
Link25	0.0000	0.1477	1337.6250	0.0000
orifice_1	0.0000	0.0000	254.6500	0.0000

 | Table E15 - SPREADSHEET INFO LIST |
 | Conduit Flow and Junction Depth Information for use in |
 | spreadsheets. The maximum values in this table are the |
 | true maximum values because they sample every time step. |
 | The values in the review results may only be the |
 | maximum of a subset of all the time steps in the run. |
 | Note: These flows are only the flows in a single barrel. |

Junction	Conduit Invert	Maximum Maximum	Total	Maximum	Maximum	##
----------	-------------------	--------------------	-------	---------	---------	----

Name	Name Elevation (m)	Flow Elevation (cms) (m)	12851_Storm Flow (m^3)	Model.out Velocity (m/s)	Volume (m^3)	##
-----	-----	-----	-----	-----	-----	##
MH 1a	P4a-4c 938.5150	1.0988 938.6092	7720.3393	2.6896	5.9985	##
MH 1e	P3f-4a 938.5140	1.0956 938.6251	7726.0601	1.3120	40.6093	##
MH 1f	P3e-3f 937.7720	0.4336 937.9362	3030.8882	1.4607	8.7386	##
MH 1b	P3d-3e 937.7780	0.3327 937.9254	1828.1732	1.3385	7.6675	##
MH 1d	P3c-3f 937.2230	0.6793 937.3152	4696.1797	2.6734	3.6251	##
MH 1c	P2-4c 936.4140	0.7053 936.6654	5000.5206	2.2150	4.4947	##
MH 1g	P1h-2 936.5100	0.5254 936.6284	3932.0568	2.1439	2.4980	##
MH 1h	P1g-3c 936.0620	0.3763 936.2338	2410.1509	1.6087	7.6456	##
MH 3a	P1f-1g 935.3190	0.3823 935.4360	2411.1793	1.4138	7.3829	##
MH 3d	P1e-1f 935.2950	0.1830 935.4475	960.2296	1.0981	4.7365	##
MH 2	P1c-1h 934.4470	0.4028 934.6311	3254.4150	2.8956	0.9166	##
MH 3b	P1b-1c 934.2770	0.2972 934.4281	2591.3238	1.2713	6.2882	##
MH 3e	P1a-1b 934.2610	0.1338 934.4363	1063.3792	0.9695	4.4061	##
MH 4b	P3b-3c 933.6260	0.3269 933.7126	2298.3885	1.3542	6.0283	##
	P3a-3b	0.2007	1160.9923	1.1336	5.1117	##

12851_Storm Model.out

MH 3f	932.5190	932.7683				
MH 3c	P4c-4d 932.6590	1.8263 932.9997	13198.6452	1.6802	81.7615	##
MH 4a	P1d-1c 932.3120	0.1402 932.7475	663.2812	1.1273	1.5756	##
MH 4c	P4b-4c 932.2360	0.1127 932.5975	486.6271	0.9835	1.6830	##
MH 4d	Link25 930.5000	0.0582 931.6570	3556.4134	7.2694	0.0004	##
Orifice	Orifice_1 930.4970	0.0582 930.5337	3557.2720	2.1319	4.4580	##
Node22	FREE # 1 925.5000	0.0582 925.5157	3556.3142	0.0000	0.0000	##

=====

Table E15a - SPREADSHEET REACH LIST Peak flow and Total Flow listed by Reach or those conduits or diversions having the same upstream and downstream nodes.
--

=====

Upstream Node	Downstream Node	Maximum Flow (cms)	Total Flow (m^3)
-----	-----	-----	-----
MH 4a	MH 4c	1.0988	7720.3393
MH 3f	MH 4a	1.0956	7726.0601
MH 3e	MH 3f	0.4336	3030.8882
MH 3d	MH 3e	0.3327	1828.1732
MH 3c	MH 3f	0.6793	4696.1797
MH 2	MH 4c	0.7053	5000.5206

12851_Storm Model.out			
MH 1h	MH 2	0.5254	3932.0568
MH 1g	MH 3c	0.3763	2410.1509
MH 1f	MH 1g	0.3823	2411.1793
MH 1e	MH 1f	0.1830	960.2296
MH 1c	MH 1h	0.4028	3254.4150
MH 1b	MH 1c	0.2972	2591.3238
MH 1a	MH 1b	0.1338	1063.3792
MH 3b	MH 3c	0.3269	2298.3885
MH 3a	MH 3b	0.2007	1160.9923
MH 4c	MH 4d	1.8263	13198.6452
MH 1d	MH 1c	0.1402	663.2812
MH 4b	MH 4c	0.1127	486.6271
orifice	Node22	0.0582	3556.4134
MH 4d	orifice	0.0582	3557.2720

```
#####
# Table E16. New Conduit Information Section #
# Conduit Invert (IE) Elevation and Conduit #
# Maximum Water Surface (WS) Elevations #
#####
```

12851_Storm Model.out						
Conduit Name		Upstream Node	Downstream Node	IE Up	IE Dn	WS Up
WS Dn	Conduit Type					
932.5975	P4a-4c Circular	MH 4a	MH 4c	932.3170	932.2360	932.7475
932.7475	P3f-4a Trapezoid	MH 3f	MH 4a	932.5240	932.3120	932.7683
933.7260	P3e-3f Trapezoid	MH 3e	MH 3f	934.2610	933.5510	934.4363
934.4363	P3d-3e Trapezoid	MH 3d	MH 3e	935.2950	934.2610	935.4475
932.7683	P3c-3f Circular	MH 3c	MH 3f	932.6770	932.5190	932.9997
932.6246	P2-4c Trapezoid	MH 2	MH 4c	934.4470	932.4410	934.6311
934.8922	P1h-2 Trapezoid	MH 1h	MH 2	936.0810	934.7400	936.2338
932.9997	P1g-3c Trapezoid	MH 1g	MH 3c	936.5100	932.6590	936.6284
936.9256	P1f-1g Trapezoid	MH 1f	MH 1g	937.7720	936.7620	937.9362
937.9362	P1e-1f Trapezoid	MH 1e	MH 1f	938.5140	937.7880	938.6251
936.2338	P1c-1h Circular	MH 1c	MH 1h	936.4140	936.0620	936.6654
936.9351	P1b-1c Trapezoid	MH 1b	MH 1c	937.7780	936.7880	937.9254
937.9254	P1a-1b Trapezoid	MH 1a	MH 1b	938.5150	937.7780	938.6092
933.7236	P3b-3c Trapezoid	MH 3b	MH 3c	934.2770	933.5730	934.4281
934.4281	P3a-3b Trapezoid	MH 3a	MH 3b	935.3190	934.2770	935.4360

12851_Storm Model.out

932.3771	P4c-4d Trapezoid	MH 4c	MH 4d	932.2410	932.0220	932.5975
936.7814	P1d-1c Trapezoid	MH 1d	MH 1c	937.2230	936.6900	937.3152
933.3518	P4b-4c Trapezoid	MH 4b	MH 4c	933.6260	933.2660	933.7126
925.5157	Link25 Circular	Orifice	Node22	930.5000	925.5000	930.5337
930.5337	Orifice_1 Circ Orif	MH 4d	orifice	930.5000	930.4970	931.6570

```

*=====
  Table E18 - Junction Continuity Error.  Division by Volume added 11/96
  Continuity Error = Net Flow + Beginning Volume - Ending Volume
                    -----
                    Total Flow + (Beginning volume + Ending volume)/2

  Net Flow    = Node Inflow - Node Outflow
  Total Flow = absolute (Inflow + Outflow)
  Intermediate column is a judgement on the node continuity error.

  Excellent < 1 percent      Great 1 to 2 percent    Good 2 to 5 percent
  Fair 5 to 10 percent      Poor 10 to 25 percent   Bad 25 to 50 percent
  Terrible > 50 percent
*=====

```

Flow Node	Junction Total Flow Name Thru Node	<-----Continuity Error -----> Failed to Volume Converge	% of Node	% of Inflow	Remaining Volume	Beginning Volume	Net Thru
0.8640	MH 1a 2127.6873	-0.6198 0	-0.0291	0.0047	1.4839	0.0000	
1.9723	MH 1e 1922.4998	1.0482 0	0.0545	0.0079	0.9240	0.0000	
1.9535	MH 1f 4824.1622	-1.2921 0	-0.0268	0.0097	3.2456	0.0000	
6.5879	MH 1b 5189.1587	2.3879 0	0.0460	0.0180	4.2000	0.0000	
0.9628	MH 1d 1327.5012	0.5475 0	0.0412	0.0041	0.4153	0.0000	

12851_Storm Model.out

0.2297	MH 1c 6509.0199	-3.0607 0	-0.0470	0.0231	3.2903	0.0000
0.9347	MH 1g 4821.3302	-7.6255 0	-0.1580	0.0575	8.5602	0.0000
1.2967	MH 1h 7865.2866	-0.1410 0	-0.0018	0.0011	1.4377	0.0000
1.1911	MH 3a 2323.2359	-0.7818 0	-0.0336	0.0059	1.9729	0.0000
1.5112	MH 3d 3657.9174	-0.9100 0	-0.0249	0.0069	2.4212	0.0000
5.0252	MH 2 10005.8656	1.0599 0	0.0106	0.0080	3.9653	0.0000
4.1875	MH 3b 4600.8824	0.6470 0	0.0141	0.0049	3.5405	0.0000
4.8878	MH 3e 6066.5248	0.5388 0	0.0089	0.0041	4.3490	0.0000
0.7386	MH 4b 973.9463	0.4442 0	0.0456	0.0034	0.2944	0.0000
1.0585	MH 3f 15453.1280	-3.9020 0	-0.0252	0.0294	4.9606	0.0000
12.2599	MH 3c 9404.7192	4.1904 0	0.0445	0.0316	8.0696	0.0000
5.6008	MH 4a 15446.3993	2.3222 0	0.0150	0.0175	3.2786	0.0000
8.9905	MH 4c 26406.1322	1.1385 0	0.0043	0.0086	7.8520	0.0000
9641.8191	MH 4d 16755.9172	1034.7380 0	4.9134	7.8044	8607.0811	0.0000
0.9299	Orifice 7113.6853	-1.4073 0	-0.0198	0.0106	2.3373	0.0000
0.1057	Node22 7112.7276	0.0232 0	0.0003	0.0002	0.0825	0.0000

12851_Storm Model.out

The total continuity error was 1029.3 cubic meters
 The remaining total volume was 8673.8 cubic meters
 Your mean node continuity error was Excellent
 Your worst node continuity error was Fair

=====

Table E19 - Junction Inflow & Outflow Listing
Units are either ft^3 or m^3
depending on the units in your model.

=====

RNF Layer	Constant	User	Interface	DWF	Inflow
Inflow	Junction	Inflow	Inflow	Inflow	through
to Node	Outflow	Evaporation	from	to Node	outfall
to Node	Name	to Node	to Node	to Node	
	from Node	from Node	2D Layer		
0.0000	MH 1a	0.0000	0.0000	0.0000	0.0000
	0.0002	0.0000	0.0000		
0.0000	MH 1e	0.0000	0.0000	0.0000	0.0000
	0.0004	0.0000	0.0000		
0.0000	MH 1f	0.0000	0.0000	0.0000	0.0000
	-0.0122	0.0000	0.0000		
0.0000	MH 1b	0.0000	0.0000	0.0000	0.0000
	-0.0045	0.0000	0.0000		
0.0000	MH 1d	0.0000	0.0000	0.0000	0.0000
	0.0004	0.0000	0.0000		
0.0000	MH 1h	0.0000	0.0000	0.0000	0.0000
	0.0007	0.0000	0.0000		
0.0000	MH 3a	0.0000	0.0000	0.0000	0.0000
	0.0004	0.0000	0.0000		
0.0000	MH 3d	0.0000	0.0000	0.0000	0.0000
	0.0007	0.0000	0.0000		
0.0000	MH 2	0.0000	0.0000	0.0000	0.0000
	0.0006	0.0000	0.0000		
0.0000	MH 3b	0.0000	0.0000	0.0000	0.0000
	-0.0094	0.0000	0.0000		
0.0000	MH 3e	0.0000	0.0000	0.0000	0.0000
	-0.0154	0.0000	0.0000		

12851_Storm Model.out

0.0000	MH 4b	0.0000	0.0000	487.3232	0.0000	0.0000
	0.0004	0.0000	0.0000	0.0000		
0.0000	Node22	0.0000	0.0000	0.0000	0.0000	0.0000
	3556.3142	0.0000	0.0000	0.0000		

=====

Table E20 - Junction Flooding and Volume Listing.
The maximum volume is the total volume in the node including the volume in the flooded storage area. This is the max volume at any time. The volume in the flooded storage area is the total volume above the ground elevation, where the flooded pond storage area starts.
The fourth column is instantaneous, the fifth is the sum of the flooded volume over the entire simulation
Units are either ft^3 or m^3 depending on the units.

=====

cell				Out of		Passed to 2D
Stored	Junction	Surcharged	Flooded	1D-System	Maximum	OR volume
Flood	Name	Time (min)	Time(min)	(Flooded	Volume	in allowed
1D-System				Volume)		Pond of
-----	-----	-----	-----	-----	-----	
0.0000	MH 1a	0.0000	0.0000	0.0000	0.1150	
0.0000	MH 1e	0.0000	0.0000	0.0000	0.1356	
0.0000	MH 1f	0.0000	0.0000	0.0000	0.2003	
0.0000	MH 1b	0.0000	0.0000	0.0000	0.1798	
0.0000	MH 1d	0.0000	0.0000	0.0000	0.1125	
0.0000	MH 1c	0.0000	0.0000	0.0000	0.3067	
0.0000	MH 1g	0.0000	0.0000	0.0000	0.1445	

		12851_Storm	Model.out	
0.0000	MH 1h	0.0000	0.0000	0.2096
0.0000	MH 3a	0.0000	0.0000	0.1428
0.0000	MH 3d	0.0000	0.0000	0.1860
0.0000	MH 2	0.0000	0.0000	0.2246
0.0000	MH 3b	0.0000	0.0000	0.1843
0.0000	MH 3e	0.0000	0.0000	0.2139
0.0000	MH 4b	0.0000	0.0000	0.1057
0.0000	MH 3f	0.0000	0.0000	0.3041
0.0000	MH 3c	0.0000	0.0000	0.4156
0.0000	MH 4a	0.0000	0.0000	0.5313
0.0000	MH 4c	0.0000	0.0000	0.4410
0.0000	MH 4d	0.0000	0.0000	8598.9023
0.0000	orifice	0.0000	0.0000	0.0448
0.0000	Node22	0.0000	0.0000	0.0191

=====

| Simulation Specific Information |

=====

Number of Input Conduits.....

21

Number of Natural Channels.....

19 Number of Simulated Conduits.....

0 Number of Junctions.....

12851_Storm Model.out

21
 Number of Storage Junctions..... 1 Number of Weirs.....
 0
 Number of Orifices..... 1 Number of Pumps.....
 0
 Number of Free Outfalls..... 1 Number of Tide Gate Outfalls.....
 0

```
*=====*
```

Average % Change in Junction or Conduit is defined as:	
Conduit % Change ==>	$100.0 \left(\frac{Q(n+1) - Q(n)}{Q_{full}} \right)$
Junction % Change ==>	$100.0 \left(\frac{Y(n+1) - Y(n)}{Y_{full}} \right)$

```
*=====*
```

The Conduit with the largest average change was..P4c-4d with 0.000 percent
 The Junction with the largest average change was.MH 4d with 0.004 percent
 The Conduit with the largest sinuosity was.....Orifice_1 with 1.788

```
*=====*
```

Table E21. Continuity balance at the end of the simulation	
Junction Inflow, Outflow or Street Flooding	
Error = Inflow + Initial Volume - Outflow - Final	Volume

```
*=====*
```

Inflow Junction	Inflow volume, m^3	Average Inflow, cms
MH 1a	1064.3081	0.0123
MH 1e	962.2702	0.0111
MH 1f	1452.7533	0.0168
MH 1b	1534.4557	0.0178
MH 1d	664.2200	0.0077
MH 1h	678.8148	0.0079
MH 3a	1162.2435	0.0135
MH 3d	1829.7441	0.0212
MH 2	1073.2882	0.0124

12851_Storm Model.out

MH 3b	1141.5016	0.0132
MH 3e	1207.4634	0.0140
MH 4b	487.3192	0.0056
MH 1a	-0.0002	0.0000
MH 1e	-0.0004	0.0000
MH 1d	-0.0004	0.0000
MH 1h	-0.0007	0.0000
MH 3a	-0.0004	0.0000
MH 3d	-0.0007	0.0000
MH 2	-0.0006	0.0000
MH 4b	-0.0004	0.0000
Node22	-3556.3142	-0.0412

Outflow Junction	Outflow Volume m^3	Average Outflow, cms
MH 1a	0.0002	0.0000
MH 1e	0.0004	0.0000
MH 1d	0.0004	0.0000

12851_Storm Model.out

MH 1h	0.0007	0.0000
MH 3a	0.0004	0.0000
MH 3d	0.0007	0.0000
MH 2	0.0006	0.0000
MH 4b	0.0004	0.0000
Node22	3556.3142	0.0412

=====

| Initial system volume = 0.0000 Cu M |

| Total system inflow volume = 13258.6762 Cu M |

| Inflow + Initial volume = 13258.6762 Cu M |

=====

| Total system outflow = 3556.3181 Cu M |

| Volume left (Final volume) = 8673.7618 Cu M |

| Evaporation = 0.0000 Cu M |

| Outflow + Final Volume = 12230.0799 Cu M |

=====

```
*=====*
| Total Model Continuity Error
| Error in Continuity, Percent =      7.7579 |
| Error in Continuity, m^3      =     1028.596 |
| + Error means a continuity loss, - a gain
*=====*
```

```
#####
# Table E22. Numerical Model judgement section #
#####
```

Overall error was (minimum of Table E18 & E21) 7.7579 percent

worst nodal error was in node MH 4d with 6.1751 percent

of the total inflow this loss was 7.8042 percent

Your overall continuity error was Fair

Excellent Efficiency

Efficiency of the simulation 1.06

Most Number of Non Convergences at one Node 0.

12851_Storm Model.out

Total Number Non Convergences at all Nodes 0.

Total Number of Nodes with Non Convergences 0.

====> Hydraulic model simulation ended normally.
====> XP-SWMM Simulation ended normally.

====> Your input file was named : C:_models\12851_Medicine V\12851_Storm Model.DAT

====> Your output file was named : C:_models\12851_Medicine V\12851_Storm Model.out

```
*=====*
```

SWMM Simulation Date and Time Summary			
Starting Date...	July	10, 2009	Time... 14: 8:49: 3
Ending Date...	July	10, 2009	Time... 14: 8:57:56
Elapsed Time...	0.14217 minutes or		8.53000 seconds

```
*=====*
```